

Item no.: 312597

APOE03 - Redundant Industrial PoE Injector

from **10,11 EUR**

Item no.: 312597
 shipping weight: 0.10 kg
 Manufacturer: ALFA Network



Product Description

APOE03 Alfa Power over Ethernet (PoE) Redundant Industrial

The APOE03 Power over Ethernet (PoE) Passive Injector delivers both data and electrical power to passive PoE devices using a single Ethernet cable. Using PoE you can eliminate the need to place an Ethernet device, such as a wireless access point or IP camera giving you more freedom. The installation of the APOE03 is simple and easy, it does not require any tools or software. Plug the APOE03 into a power outlet and connect the APOE03 to your passive PoE device using any standard Ethernet cable. Once the APOE03 setup has been completed, the output power is compatible to any 5 V DC, 12 V DC, 24 V DC, 48 V DC, 57 V DC (max. 48 W) Passive PoE-enabled device.

Product Features:

- Supports Fast Ethernet Passive PoE-enabled devices (PIN 1/2/3/4 Data. PIN 4/5/7/8 Power)
- Provides both data and electrical power to Passive PoE-enabled devices
- Supports a wide range of input/output DC power (5 - 57 V at max. 48 W)
- Dual DC power input – 3-pin Screw Terminal Block and Power Jack
- Wall mount ability
- Power: PIN 4/5, 7/8
- Data: PIN 1/2, 3/6
- Data In: Connects PC/HUB/Switch
- Ethernet data rate: 10/100TX Mbps
- Ethernet cable: Cat.5 / Cat.5e / Cat.6
- Ethernet cable connector: RJ45
- Support input voltage: 5 - 57 V (max. 48 W)
- Support output voltage: 5 - 57 V (max. 48 W)
- Built-in LED indicators: Power
- Operating temperature: -0°C ~ 40°C
- Storage temperature: -20°C ~ 60°C
- Operating humidity: 10% to 80% non-condensing
- Storage humidity: 5% to 90% non-condensing
- Power supply: 110 - 220 V AC; 5 - 57 V DC input
- Unit dimensions: 67 x 67 x 24 mm (W x L x H)
- Unit weight: 40 g

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

