

Item no.: PRA50021U

PRA5021-E - 5 GHz, 21 dBi Panel Antenna + Enclosure



from **28**,62 EUR

Item no.: PRA50021U shipping weight: 1.40 kg Manufacturer: ITELITE

Product Description

IT ELITE PRA50021 - 5 GHz, 21 dBi Panel Antenna + Enclosure

PRA50021 is a compact, weatherproof outdoor enclosure (IP66/67) featuring a panel 5 GHz antenna operating from 5.1 GHz to 5.9 GHz with a steady gain of 21 dBi across the

Specifically designed for operation under severe weather conditions, since proper materials allow operation without the risk of corrosion even in saltwater environments. High-quality construction of the pole mounting elements guarantee an easy elevation and tilt adjustment, as well as rock-stable operation.

It can be used as a client station and as a small base station. The enclosure is compatible with MikroTik RouterBOARDs of the 411 and 433 series. Key Features:

- 21 dBi gain
- 21 dbl garr
 Highest Ingress Protection Rating IP 66/67
 High-quality construction
 Ultra low sidelobes
 Horizontal or vertical polarization

- Heavy-duty mounting elements
- Easy elevation and tilt adjustmentSpecial outdoor weatherproof enclosure
- Suitable for Mikrotik RouterBOARDs

Applications

- 5 GHz band Wireless LANIEEE 802.11a WLAN systems
- RLAN FWA
- WiMAX

Electrical Properties

- Frequency: 5.1 5.9 GHz
- Gain: 21 dBiPolarization: Horizontal or vertical
- Beamwidth deg horizontal: 15°
 Beamwidth deg vertical: 15°

- Impedance: 50 ohms
 Front-to-back ratio: > 35 dB

Mechanical Properties

- Material: ABS
 Color: Grey
 Ingress Protection Rating (EN 60529): IP66/67
 Weight: 1.2 kg
 Dimensions: 270 x 270 x 75 mm
 Inside dimensions: 255 x 255 x 35mm
 Min. temperature °C (short term): -40
 Max. temperature °C (short term): 120
 Input connector: SMA female, optional U.FL or MMCX pigtail
 Mounting kit: 50.8 mm / 2"
 Distance pieces for board:

- Distance high: 19 mm
 Material thickness of the board: 1,6 mm
 Borehole: 4 mm

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

