

Item no.: SECTOR-23015V

## SEC2315V - 2.3 GHz, 15 dBi Outdoor Sector Antenna



### 40,20 EUR

Item no.: SECTOR-23015V  
shipping weight: 1.60 kg  
Manufacturer: ITELITE

### Product Description

#### IT ELITE SEC23015V - 2.3 GHz, 15 dBi Outdoor Sector Antenna

Sector antenna working in the 2.3 GHz band with 15 dBi gain and vertical polarization. Because of reduced sidelobes, the antenna keeps a clear, strong signal even in crowded radio environments. It's resistant to interference from other networks and does not disrupt others. The antenna features no beam squint due to frequency change, this means that decreasing of data throughput or even loss of a link after frequency channel change does not occur.

Specifically designed for operation under severe weather conditions, since proper materials allow operation without the risk of corrosion even in saltwater environments. Professional mounting system with 0-15 degrees scale guarantees easy and smooth tilt adjustment, as well as rock-stable operation.

Key Features:

- 15 dBi sectorial gain
- Special outdoor weatherproof enclosure
- Highest International Protection Rating IP 66
- High-quality construction
- Minimized sidelobe levels
- Vertical polarization
- Heavy-duty mounting elements
- Easy elevation and tilt adjustment
- Designed for all-weather operation

Applications:

- WCS band 2.3 - 2.36 GHz
- Point-to-multipoint applications

Electrical Properties

- Frequency: 2.3 – 2.36 GHz
- Gain: 15 dBi
- Polarization: Horizontal or vertical
- Beamwidth deg horizontal: 90°
- Beamwidth deg vertical: 12°
- VSWR:
- Impedance: 50 Ohm
- Front-to-back ratio: >35 dB

Enclosure Properties

- Technology: Microstrip
- Material: UV-resistant
- Color: White
- Ingress Protection Rating (EN 60529): IP 66
- Min. temperature: -40°C
- Max. temperature: 120°C

Mechanical Properties

- Input connector: N-type / female
- Outside dimensions: 580 x 125 x 50 mm
- Weight: 1.5 kg

## Specifications

---

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

