

Item no.: 312819

RBA-06-AD2-CAX-A1 - Wall-mounted 19" cabinet, 2-sectioned, 6 HU, 295 mm depth

from 215,06 EUR

shipping weight: 13.00 kg Manufacturer: Triton



Product Description

TRITON RBA-06-AD2-CAX-A1 - Wall-mounted 19" cabinet, 2-sectioned, 6 HU, 295 mm depth

The data and telecommunication cabinet is a very successful version of two-sectioned cabinets. The front part of the cabinet which can be opened enables an easy access to the rear cabinet section.

The cabinet has a robust welded construction. High-quality processing and up-to-date technologies ensure a perfect look of the cabinet.

The cabinet door is glass by default but can be steel or perforated if required. The hinge system enables an almost 180° wide opening of the door. The door can be easily removed and mounted for changing the door opening direction.

EASY ACCESS:

The front part of the cabinet which can be opened enables an easy access to the rear cabinet section. You can easily remove the front part of the cabinet after unlocking chain shackles. All parts are interconnected and grounded.

ADJUSTABLE VERTICAL RAILS:

One pair of vertical 19 rails is freely adjustable in any depth of the cabinet. This simplifies mounting the devices and organizing connecting cables.

BREAKOUT-TYPE BLANKING PANELS:

Cable openings covered with breakout-type blanking panels are ready in the top, bottom and rear part of the cabinet. Use a plastic frame and a blanking panel with a brush that are part of the cabinet supply to seal the cabinet opening against dust. Size in mm:

• 370 x 600 x 295

Description, usage

- 19 two-sectioned wall-mounted cabinet with IP 30 protection
- Cabinet is to be hanged right on the wall
 Cabinet components include two sliding vertical rails
- Cabinet construction:Compact welded cabinet
 - Glass door: safety hardened glass, thickness 5 mm
- Cabinets are intended for installing data and telecommunication devices and their distribution systems The frame of the cabinet and all removable parts are connected with grounding cables that have to be properly fixed and inserted into connectors during all the time when using the cabinet
- There is one M8 screw placed on the bottom part of the cabinet as a main grounding point
- Cable openings covered with breakout-type blanking panels are placed in the top and the bottom part of the cabinet's rear side, others are in the top and the bottom side of the cabinet

Supply includes:

- Key front door 2x
- Screw 6x50 4x Washer 6.6 4x
- Dowel 10 4x
- Captive nut M6 8x
- Blanking panel with brush 1x

Material:

- Safety hardened glass 5 mm thickSteel sheet

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

