

Item no.: OMNITIK-5-POE-AC

RBOMNITIKPG-5HACD - OmniTik 5 PoE ac with 2 x 7.5 dBi 5 GHz omni antennas

from **135,64 EUR**

Item no.: OMNITIK-5-POE-AC

shipping weight: 1.50 kg

Manufacturer: MikroTik



Product Description

MikroTik OmniTik 5 PoE ac with 2 x 7.5 dBi 5 GHz omni antennas

MikroTik is introducing a significant upgrade to their popular OmniTik 5 GHz access points.

OmniTik 5 PoE ac features five Gigabit Ethernet ports and support for 802.11ac. Its equipped with a powerful 720 MHz CPU, 128 MB RAM, high- power 1.300 mW 802.11a/n/ac dual-chain wireless (support for AC as well as backwards compatible with regular 802.11a/n CPE) and comes with a new design weatherproof outdoor enclosure, two integrated 7.5 dBi 5 GHz omni antennas, a power supply, a PoE injector and a mounting kit.

OmniTik 5 PoE supports passive or standard 802.3at/af PoE input/output (12 - 57 V). Ethernet ports 2-5 can power other PoE capable devices with the same voltage as applied to the unit. Less power adapters and cables to worry about! It can power 48 V devices (like IP camera), if 48V input is used.

Attention! This device needs to be upgraded to RouterOS v6.46 or the latest version to ensure compliance with local authority regulations!

- CPU: QCA9557 720 MHz
- Memory: 128 MB
- Storage type: Flash
- Storage size: 16 MB
- Ethernet: 5x 10/100/1000 Mbit/s Fast Ethernet ports with Auto-MDI/X
- Wireless: QCA9892, wireless built-in 5 GHz 802.11ac, dual-chain
- Frequency range: 5150 - 5875 MHz
- Power options: PoE input, passive 12 - 57 V
- PoE out: Yes, Ether2 - Ether5
- Max output per port: 1 A (if input < 30 V), 0.5 A (if input > 30 V)
- Consumption: 18 W
- Antenna gain: 7.5 dBi
- Antenna beam width: 360°
- USB: 1x USB type A
- Dimensions: 416 x 129 x 58 mm
- Operating temperature: -40°C to +70°C tested
- LEDs: 10x LEDs
- License level: 4
- Operating system: RouterOS

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

