

Item no.: CRS328-4C-20S-4S+RM

CRS328-4C-20S-4S+RM - Cloud Router Switch with 800 MHz CPU, 512 MB RAM

from 421,45 EUR

Item no.: CRS328-4C-20S-4S+RM shipping weight: 2.60 kg Manufacturer: MikroTik



Product Description

MikroTik CRS328-4C-20S-4S+RM - Cloud Router Switch with 800 MHz CPU, 512 MB RAM

The CRS328-4C-20S-4S+RM is a 28 independent port switch with a combo group.

This device has twenty SFP ports, four SFP+ ports for 10G modules and four combo ports, where you can choose to use SFP or RJ45 ports from the combo group. These ports can also be software selected, so if you have plugged in all eight cables, you can use scripting to decide which four combo ports will be active.

The device comes in a 1U rackmount case with two 100-240 V power supplies with fail-over functionality. An RJ45 console port is available for management and debugging, and a mode button can be customised to execute any RouterOS commands.

The device has a dual boot feature that allows you to choose between two operating systems - RouterOS or SwOS.

If you prefer to have a simplified operating system with only switch specific features, use SwOS. If you would like the ability to use routing and other Layer 3 features in your CRS, use RouterOS. You can select the desired operating system from RouterOS, from SwOS or from the RouterBOOT loader settings.

- Product code: CRS328-4C-20S-4S+RMCPU: Marvell 8DX3236A1 800 MHz
- RAM: 512 MB
- Storage type: Flash Storage size: 16 MB
- Switch chip model: 98DX3236A1
- SFP cages: 20

- SFP+ cages: 4
 Ethernet/SFP combo ports: 4
 Operating system: SwOS / RouterOS (dual boot)
- Supported input voltage: 100 240 V Dimensions: 443 x 200 x 44 mm
- Operating temperature: -20°C to +60°C tested
- Max. power consumption: 43 W Serial port: RJ45
- License level: 5





prices and availability