

Item no.: HG3-TP-S30

## **HG3-TP-S30 - Symmetrical Horn TP Antenna Gen2**

131,34 EUR

Item no.: HG3-TP-S30 shipping weight: 3.30 kg Manufacturer: RF Elements



## Product Description

RF Elements HG3-TP-S30 - Symmetrical Horn TP Antenna Gen2Horn Antenna with TwistPort(TM) Connector

Symmetrical Horn Antennas have a symmetrical beam pattern with no side lobes. They offer excellent noise rejection and supreme scalability options. They are perfect for high-density AP clusters and dense radio co-location.

Symmetrical Horn TP Antennas Gen2 feature our industry-changing TwistPort(TM) connector, a patent-pending quick-locking waveguide port. TwistPort(TM) is virtually lossless and revolutionary easy to use.

Symmetrical Horn TP Antennas Gen2 feature multiple improvements on RF performance and industrial design, incl. an optically lighter antenna body and significantly improved antenna bracket. The radome is made of more resistant material and the whole range of Gen2 antennas only uses two different radome sizes.

- Antenna connection: TwistPort(TM) quick locking waveguide port
- Antenna type: Horn
   Materials: UV resistant ABS plastic, polycarbonate, polypropylene, aluminium, stainless steel
- Enviromental: IP55

- Enviromental: IP55
  Pole mounting diameter: 30-90 mm
  Temperature: -30°C to +55°C (-22°F to +131°F)
  Wind survival: 160 km/hour
  Wind loading: 44 N at 160 km/hour
  Mechanical tilt: +/-25°
  Weight: 3.3 kg/7.3 lbs single unit incl. package
  Dimensions: 41.2 x 27.7 x 23.4 cm single unit incl. package

## Performance

- Frequency range: 5180 6400 MHz
  Gain: 18.4 dBi
  Azimuth beam width -3 dB: H 21°/V 21°
- Elevation beam width -3 dB: H 21°/V 21°
  Azimuth beam width -6 dB: H 30°/V 30°
  Elevation beam width -6 dB: H 30°/V 30°
- Front-to-back ratio: 37 dB

## Specifications

