

Item no.: HG3-TP-S70 HG3-TP-S70 - Symmetrical Horn TP Antenna Gen2





Product Description

RF Elements HG3-TP-S70 - Symmetrical Horn TP Antenna Gen2Horn Antenna with TwistPort(TM) Connector

Symmetrical Horn Antennas have a symmetrical beam pattern with no side lobes. They offer excellent noise rejection and supreme scalability options. They are perfect for high-density AP clusters and dense radio co-location.

Symmetrical Horn TP Antennas Gen2 feature our industry-changing TwistPort(TM) connector, a patent-pending quick-locking waveguide port. TwistPort(TM) is virtually lossless and revolutionary easy to use.

Symmetrical Horn TP Antennas Gen2 feature multiple improvements on RF performance and industrial design, incl. an optically lighter antenna body and significantly improved antenna bracket. The radome is made of more resistant material and the whole range of Gen2 antennas only uses two different radome sizes.

- Antenna connection: TwistPort(TM) quick locking waveguide port
- Antenna type: Horn
 Materials: UV resistant ABS plastic, polycarbonate, polypropylene, aluminium, stainless steel
- Enviromental: IP55

- Environmental: IP55
 Pole mounting diameter: 30-90 mm
 Temperature: -30°C to +55°C (-22°F to +131°F)
 Wind survival: 160 km/hour
 Wind loading: 22 N at 160 km/hour
 Mechanical tilt: +/-25°
 Weight: 2.2 kg/4.8 lbs single unit incl. package
 Dimensions: 30.5 x 23.9 x 18.3 cm single unit incl. package

Performance

- Frequency range: 5180 6400 MHz
 Gain: 11.5 dBi
 Azimuth beam width -3 dB: H 50°/V 50°

- Azimuth beam width -3 dB: H 50°/V 50°
 Azimuth beam width -6 dB: H 70°/V 70°
 Elevation beam width -6 dB: H 70°/V 70°
- Front-to-back ratio: 30 dB

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

