

Item no.: 323556

WISP-NR - 802.11n WISP Indoor Router (24V Passive PoE for 1x(LAN+WAN))

from **42,98 EUR**

Item no.: 323556
shipping weight: 0.40 kg
Manufacturer: ALFA Network



Product Description

ALFA Network - 802.11n WISP Indoor Router (24V Passive PoE for 1x(LAN+WAN))

24V Passive PoE Out on both WAN & LAN 1 Ports. Power Outdoor AP/CPE without an extra Power source.

WISP-NR is a unique wireless gateway specially designed for Wireless ISPs which supports Wi-Fi 802.11n 300Mbps and has passive 24VDC PoE output from both the WAN and LAN1 ports. It is easy for WISP installers to power outdoor AP/CPE without an additional power source. 802.11n 300Mbps 2.4GHz technology allows users to use their mobile device or laptop to connect and enjoy high speed Internet access. Work with:

- Ubiquiti
- Mikrotik
- EnGenius
- TP-Link
- ALFA
- Other Passive 24v PoE devices

Package content

- WISP-NR
- 24V /1A Power adapter
- 2x 5dBi detachable antenna
- QIG
- Wi-Fi Standard:
- IEEE 802.11b
- IEEE 802.11g
- IEEE 802.11n
- Frequency: 2.400-2.483 GHz
- Channel Width: 20/40 MHz
- Data Rate:
- 802.11b: up to 12 Mbps
- 802.11g: up to 54 Mbps
- 802.11n: up to 300 Mbps
- Antenna: 2.4 GHz 5 dBi dipole
- Antenna connector: RP-SMA female
- 24 V PoE Output Port: WAN, LAN 1
- LED: PWR, SYS, WAN, LAN, WPS
- Interface:
- 1x 10/100 WAN
- 4x 10/100 LAN
- 1x Reset button
- 1x WPS button
- 1x DC jack
- Security:
- 64/128bit WEP
- WPA-PSK
- WPA-EAP (PEAP/TLS)
- WPA2-PSK
- WPA2-EAP
- WPA Mixed
- 802.1x authentication
- TX output:
- 802.11b: up to 26+/-1 dBm
- 802.11g: up to 24+/-1 dBm
- 802.11n: up to 24+/-1 dBm
- RX sensitivity:
- -96 dBm (at) 802.11b
- -91 dBm (at) 802.11g
- -91 dBm (at) 802.11n
- Power adapter: 24 V DC / 1 A
- Operation Temperature: -30°C ~ 60°C
- Storage Humidity: 10% ~ 90% (Non-condensing)
- Dimension(mm): 147 x 98 x 30 mm
- Weight: 0.4 kg

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

