

Item no.: PDU41004

## PDU41004 - Switched Series Power Distribution Unit, 230 V/15 A, 1 U, 8x IEC Outlet

from **369,91 EUR**

Item no.: PDU41004  
 shipping weight: 2.10 kg  
 Manufacturer: CyberPower



### Product Description

Cyberpower PDU41004 - Switched Series Power Distribution Unit, 230 V/15 A, 1 U, 8x IEC Outlet

CyberPower PDU41004 provides output from a UPS unit, generator, or utility power to multiple connected devices in IT environments. The unit supports remote individual outlet control over the network, allowing administrators to turn on/off connected devices from any location. Administrators can further determine the power sequence used to turn individual outlets on or off. The Daisy Chain function also allows the PDUs connected together to be monitored and controlled under one IP address.

The LCD display delivers vital information for users, allowing easy maintenance and monitoring of PDU.

The power management web interface offers real-time remote monitoring of the PDU vitals of the networked clients' outlets. Event logging via a web browser or network connection allows users to review a history of power conditions. When specified power events occur, automatic event notifications will be sent via email, SMS text, or SNMP trap to designated users so that they can take immediate actions. The featured RJ45 port enables the connection of the optional environmental sensor (ENVIROSENSOR), which can provide real-time temperature and humidity monitoring in an IT center.

#### Input

- Nominal input voltage (Vac): 100 ~ 240
- Input frequency (Hz): 50/60
- Maximum input current (A): 12 (UL), 10 (CE)
- Input connector type: 1x IEC C14
- Power cord length (m.): 3.05

#### Output

- Over current protection (each bank) (A): -
- Outlets, # of bank(s) (bank): 1
- Outlet(s), total: 8
- Outlet(s), front: 8
- Outlet type: 8x IEC C13

#### Management & Communications

- LCD information display: Input voltage (Volts), input frequency (Hz), current level (Amps), power consumption (Kilowatts), network information, serial number, environment status, hardware version, firmware version
- LED indicators: PDU status, Tx/Rx, link, outlet
- Environmental sensor supported: Yes
- Power management software: PowerPanel(R) Business Edition
- Supported protocols: IPv4/v6, SNMPv1/v3, HTTP/HTTPS, TCP/IP, UDP, DHCP, NTP, DNS, SMTP, SSH, SSL, TLS, Telnet, FTP, and Syslog
- Authentication: RADIUS, LDAP, LDAPS, Windows AD

#### Physical

- Installed rack height (U): 1
- Cord retention tray: Yes
- IEC receptacle locking: Yes

#### Physical Size

- Dimensions (W x H x D) (mm): 433 x 44 x 112
- Weight (kg): 2.1

#### Environmental

- Operating temperature (°C): 0 - 55
- Operating relative humidity (non-condensing) (%): 0 - 95

#### Certifications

- Certifications: CE, FCC Class A, UL60950
- Cisco Compatibility: Yes
- RoHS: Yes

## Specifications

---

**Scan this QR code to  
view the product**

All details, up-to-date  
prices and availability

