

Item no.: 356533

## APLM2-H1 - QuPanel LTE HP MIMO 2x2, 10 m Cable

# from 101,49 EUR

shipping weight: 1.80 kg Manufacturer: QuWireless

#### Product Description

QuPanel LTE HP directional MIMO 2x2 high gain antenna is predicted for 4G LTE mainly, but is compatible with 3G and 2G as well. The antenna improves the signal in rural/suburban locations and where the mobile signal is weak. That antenna is predicted to be installed on the buildings (on the pole or on the wall). Due to very wide working frequency range, the antenna is universal client for LTE bands like LTE700/800/1800/1900/2100/2300/2600. It's compatible with Teltonika: RUT240, RUT900, RUT950, RUT955, RUTX09, RUTX11 and other MIMO 2x2 LTE/3G/2G modems and routers.

LTE Antenna Specification

- Frequency: 0.694 0.96 GHz; 1.7 2.2 GHz; 2.2 2.7 GHz
  Supported LTE/5G bands: 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53, 65, 66, 67, 68, 69, 85, 103, n80, n81, n82, n83, n84, n86, n89, n90, n95, n97, n98, n100, n101, n256
  Gain: 0.694 0.96 GHz: 7 dBi; 1.7 2.2 GHz: 7 dBi; 2.2 2.7 GHz: 7 dBi

- Front-to-back: >10 dBVSWR: <1.70, max <2.00</li>
- Beamwidth: 70°/70° ±15°
  Polarization: Dual polarized X-Pol
- Impedance: 50 ?

#### Mechanical Specifications

- Materials: ABS, aluminum, PTFE, fiberglass
- Ingress protection: IP67
  Dimensions: 272 x 276 x 96 mm (10.71 x 10.87 x 3.78 inch)
- Weight: 1.8 kg (3.97 lbs)
   Operating temperature: From -40°C to 75°C (from -40°F to 167°F)
   Cable length: 10 m

- Cable tength. 10 m
   Cable type: LMR195 white
   Connector type: 2x integrated cables with SMA plug

### Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

