

Item no.: 330553

CM2-24-58-2RPSP - Ultra Low Profile MiMo, WiFi Antenna

from **87,12 EUR**

Item no.: 330553
shipping weight: 0.30 kg
Manufacturer: Panorama Antennas



Product Description

CM2-24-58-2RPSP Ultra Low Profile MiMo, WiFi Antenna

The CM[X]-24-58-2 range has been designed to provide MiMo WiFi operation in an ultra low profile package. The compact, robust, low-profile housing contains up to four antenna elements with effective isolation and low correlation covering 2.4-2.5/4.9-6GHz.

The antenna is designed to be panel mounted on vehicles or devices and can be fitted on a conductive or non-conductive panel. Supplied with integrated flame retardant CS32 cables (Compliant to UNECE 118.01 and EN45545-2) and a halogen free flame retardant radome (white version), the antenna is suitable for many environments and applications.

Features

- Ultra Low Profile
- Up to 4 x 4 MiMo Dual Band WiFi
- Certified to EN45545-2
- Certified to EN50155
- Meets IP69K and IK10

Electrical Data

- Wifi Frequencies: 2.4/5.0GHz
- Typical VSWR:
- WiFi MiMo: 2x2
- Max Input Power (W): 10
- Pattern: Omni-directional
- Ground Plane Independent: Yes

Mechanical Data

- Available Colour: White
- Height (mm): 30
- Diameter (mm): 115
- Connector: Rev Pol SMA Plug

Mounting Data

- Mounting Type: Panel Mount
- Mounting Method: 18mm (3/4") Mounting Bush

Approvals Data

- Vandal Protection: IK10
- IP Rating: IP66/IP69K
- Flame Retardancy: UN118.01 / EN6722 / EN45545
- Industry Approvals: EN45545

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

