

Item no.: 332879

## ARCHER T3U PLUS - AC1300 High Gain Wireless Dual Band USB Adapter

from **19,15 EUR**

Item no.: 332879  
shipping weight: 0.20 kg  
Manufacturer: TP-LINK



### Product Description

#### Archer T3U Plus - AC1300 High Gain Wireless Dual Band USB Adapter AC1300 Dual Band Wi-Fi

The Archer T3U Plus receives Wi-Fi signals on two separate bands for all your online needs. Choose the 2.4 GHz band for up to 400 Mbps of surfing, emailing and social media, or switch to 5 GHz for up to 867 Mbps of gaming, HD streaming and large file downloads. Boosted Throughput with MU-MIMO

MU-MIMO technology can provide two simultaneous data streams, improving the throughput and efficiency of the entire network when working with a compatible MU-MIMO router. High Gain Antenna for Broader Coverage

A high gain antenna reaches your router from farther with more precise directional range, sustaining faster and more stable wireless connections. Adjustable Multi-Directional Antenna

Rotate and adjust the antenna in the multi-direction to improve using experience in different environments.

#### WLAN Features

- Wireless standards: IEEE 802.11b/g/n 2.4 GHz, IEEE 802.11a/n/ac 5 GHz
- Signal rate: 5 GHz: 11ac: Up to 867 Mbps (dynamic), 11n: Up to 300 Mbps (dynamic), 11a: Up to 54 Mbps (dynamic); 2.4 GHz: 11n: Up to 400 Mbps (dynamic), 11g: Up to 54 Mbps (dynamic), 11b: Up to 11 Mbps (dynamic)
- Reception sensitivity: 5 GHz: 11ac VHT80: -62 dBm, 11ac VHT40: -64 dBm, 11ac VHT20: -68 dBm, 11n HT40: -71 dBm, 11n HT20: -73 dBm, 11a 54 Mbps: -77 dBm; 2.4 GHz: 11n HT40: -70 dBm, 11n HT20: -71 dBm, 11g 54 Mbps: -73 dBm, 11b 11 Mbps: -87 dBm
- Transmit power: 5 GHz: 20 dBm (FCC)/20 dBm (CE) (EIRP); 2.4 GHz: 18 dBm (FCC)/18 dBm (CE) (EIRP)
- Wireless modes: Infrastructure mode
- Interface: USB 3.0
- Wireless security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

#### Hardware

- Antennas: 1x external high gain antenna
- LED: Status
- Dimensions: 2.28 x 0.71 x 6.83 in (57.8 x 18 x 173.4 mm)

#### Others

- Package contents: AC1300 high gain wireless dual band USB adapter, quick installation guide, resource CD
- Certification: FCC, CE, RoHS
- System requirements: Windows 10/8.1/8/7 (32/64 bit)
- Environment: Operating temperature: 0°C ~ 40°C (32°F ~ 104°F); Storage temperature: -40°C ~ 70°C (-40°F ~ 158°F); Operating humidity: 10% ~ 90% non-condensing; Storage humidity: 5% ~ 90% non-condensing

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability



