

Item no.: 332945

## TL-PA7017P KIT - AV1000 Gigabit Passthrough Powerline Starter Kit

**57,41 EUR**

Item no.: 332945  
shipping weight: 0.40 kg  
Manufacturer: TP-LINK



### Product Description

#### TL-PA7017P KIT - AV1000 Gigabit Passthrough Powerline Starter Kit 1000 Mbps - Perfect for Bandwidth-Hungry Activities

Coming with advanced HomePlug AV2 technology, TL-PA7017P KIT provides users with high-speed data transfer rates of up to 1000 Mbps - ideal for bandwidth-intensive applications such as multiple HD/3D/4K video streaming, online gaming, and large file transfers. [Gigabit Port for Ultra-Fast Data Transfer](#)

With one Gigabit Ethernet port, TL-PA7017P KIT allows users to connect a bandwidth-intensive device to the internet at high speeds, ensuring smooth streaming for Ultra HD videos. This makes the TL-PA7017P KIT the perfect home entertainment companion. [Plug and Play, No Configuration Required](#)

Connect a powerline adapter to the router. Plug another powerline adapter into a wall socket in another room. Connect it to your internet enabled device via Ethernet-and you're done!

#### Hardware

- Plug type: EU
- Standards and protocols: HomePlug AV2, HomePlug AV, IEEE 1901, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- Power consumption: Maximum: 3.26 W, Typical: 2.58 W, Standby: 0.83 W
- Compatibility: Compatible with any Powerline adapters/extenders and routers
- Coverage: Connects more devices by adding more adapters or connecting an access point or a switch
- Range: 300 meters/1,000 feet over electrical circuit
- Interface: Gigabit Ethernet port, Power socket
- Button: Pair button
- LED indicator: Power, Powerline, Ethernet
- Dimensions (W x D x H): 2.3 x 1.7 x 3.7 in (58 x 42 x 95 mm)

#### Software

- Modulation technology: OFDM (PLC)
- Encryption: Powerline security: 128-bit AES

#### Others

- Certification: CE, RoHS
- Package contents: 2x AV1000 Gigabit passthrough powerline adapter TL-PA7017P, 2x Ethernet cable, quick installation guide
- System requirements: Windows 2000/XP/2003/Vista, Windows 7/8/8.1/10, Mac, Linux
- System requirements for tpPLC Utility: Windows XP/Vista/7/8/8.1/10 and Mac OS X (10.7 or later)
- Environment: Operating temperature: 0°C ~ 40°C (32°F ~ 104°F); Storage temperature: -40°C ~ 70°C (-40°F ~ 158°F); Operating humidity: 10% ~ 90% non-condensing; Storage humidity: 5% ~ 90% non-condensing

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability



