

Item no.: 341058

XH310RV - Barebone XPC slim black

from **182,49 EUR**

Item no.: 341058
shipping weight: 3.00 kg
Manufacturer: Shuttle



Product Description

SHUTTLE Barebone XPC slim XH310RV black

XPC slim XH310RV is an affordable 3-litre PC for demanding tasks.

The Shuttle XPC Barebone XH310RV is a real versatile one considering its small footprint - one optical drive, two 2.5" storage drives and an M.2 SSD card can be installed into the robust steel chassis. Besides, it supports the powerful Intel Core desktop processors with socket LGA1151v2. The built-in heat pipe cooling ensures the system runs quietly at maximum stability. Thanks to its great connectivity it meets the requirements of many applications that extends from office PC up to industrial applications. The system supports two displays with Ultra HD resolution, dual Gigabit LAN, four USB 3.0 and four USB 2.0 ports and two serial ports. With this high level of efficiency and flexibility - who needs a bulky tower PC anyway?

Slim design

- Slim 3.5 L case, black, front flaps
- Dimensions: 24.2 x 20 x 7.25 cm (L/W/H)
- Permissible ambient temperature: 0 - 50 °C
- Mainboard in Mini-ITX format (17 x 17 cm)

Processor

- Socket LGA1151v2 supports Intel Core CPUs Gen. 8/9 "Coffee Lake" with max. 65 W TDP Core i9/i7/i5/i3, Pentium Gold, Celeron
- Supplied heat pipe cooling system

Operating system

- Supplied without operating system
- Supports Windows 10 and Linux -64 bit

Chipset

- Intel H310 chipset

Memory

- 2 x 260-pin SO-DIMM slot
- Supports DDR4-2400/2666, max. 2 x 32 GB

Graphics

- Integrated Intel UHD graphics
- Supports two 4K displays simultaneously

Drive bays

- Bays: 2 x 2.5" for hard disks or SSDs and 1x for optical SATA slimline drive
- Connectors: 3 x Serial ATA max. 6 Gb/s,
- pre-installed cables for one 2.5" drive and one ODD slimline drive

Mini-Slots

- M.2 2280M slot (supports SATA/PCIeSSDs)
- M.2 2230E slot (supports WLAN cards)

External connections

- HDMI 2.0a + DisplayPort 1.2 + D-Sub/VGA
- 5.1 HD audio (digital audio via HDMI/DP)
- 4 x USB 3.0
- 4 x USB 2.0 (2 each front/rear)
- 2 x Intel Gigabit LAN
- 2 x RS232 (1x RS422/RS485)
- Connection for external power/clear CMOS button

Onboard connections

- USB 2.0
- Embedded DisplayPort. LPC
- Connector for 12 V supply voltage
- Always-On-Jumper (Power-on-after-power-fail)

Optional accessories

- Stand (PS01)
- 3.5" bracket (PHD4)
- VESA holder (PV02)
- WLAN (WLN-M)
- DVD tray cover (MY01)
- Cable for external power button (CXP01)

Power supply

- 90W/19V adapter (DC-In also supports 12V)

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

