

Item no.: STA-SMA

## STA-SMA - StarterAdapter(TM) SMA

**19,34 EUR**

Item no.: STA-SMA  
shipping weight: 0.20 kg  
Manufacturer: RF Elements



### Product Description

#### STA-SMA - StarterAdapter(TM) SMA

The StarterAdapter(TM) SMA converts waveguide interface into coaxial RP-SMA for horizontal and vertical polarization. The adapter enables using radios with coaxial interface with any StarterDish(TM) antenna.

#### Technical Data

- Antenna connection: Waveguide port
- Radio connection: 2x RP-SMA female
- Materials: Insert - Aluminium alloy; Adapter - UV stabilized and weather resistant ABS plastic
- Flame rating: UL 94 HB
- Temperature: -40°C to +60°C (-40°F to +140°F)
- Wind survival: 160 km/h
- Weight: 0.16 kg/0.35 lbs – single unit incl. package
- Dimensions: 120 x 75 x 75 mm/4.7 x 2.9 x 2.9 inch – single unit incl. package

#### Performance

- Frequency range: 5150 - 5950 MHz
- Polarization: Dual linear H + V
- VSWR: Max. 1.8
- Impedance: 50 Ohm

#### Compatible Wireless Platforms

- RF elements(R): Any StarterDish(TM) antenna

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

