

Item no.: 349226

# BOXER-6450-TGUA2-1010 - Fanless Compact Embedded Computer, Intel® Core™ i5-1145G7E, 1.50 GHz

# from **1.056,75 EUR**

shipping weight: 1.50 kg Manufacturer: AAEON



## Product Description

Fanless Compact Embedded Computer, Intel® Core™ i5-1145G7E, 1.50 GHz

The BOXER-6450-TGU brings the capabilities of the 11th Generation Intel Core U processors to the BOXER-6400 family of ultra-compact platforms. Easy to deploy anywhere and at a cost that's friendly to almost any budget, the BOXER-6450-TGU helps users get their projects up and running quickly. Packing List

- BOXER-6450-TGU
- 2x wallmount brackets
- 1x screw package

#### System

- CPU: Intel® Core™ i5-1145G7E, 1.50 GHz

- CPU: Intel® Core™ i5-1145G7E, 1.50 GHz
  Chipset: Intel® System on Chip
  System memory: LPDDR4x max. 3200 MHz on board memory up to 32 GB
  Display interface: 1x HDMI2.0b, 4Kx2K 60 Hz
  Storage device: 1x 2.5° SATA drive bay; 1x full-size Minicard for mSATA (optional); 1x M.2 2280 NVMe slot
  Ethernet: 1x RJ-45 for 1x 2.5 GbE LAN i225-LM; 1x RJ-45 for 1x GbE LAN i219-LM
  I/O: 2x USB type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Devent of USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Type-A for USB 3.2 Gen2; 4x USB type-A for USB 3.2 Typ

- OS support: Windows® 10, Windows® 10 IoT, Ubuntu 20.04.2

### Power Supply

• Power requirement: 1x DC-in 12V for lockable DC jack

#### Mechanical

- Mounting: Wallmount
  Dimensions (W x H x D): 6.54" x 4.65" x 2.2" (166 x 118 x 56 mm)
  Gross weight: 3,3 lb (1.5 kg)
- Net weight: 2.20 lb (1 kg)

#### Environmental

- Operating temperature: 14°F ~ 131°F (-10°C ~ 55°C), IEC68-2 with 0.5 m/s AirFlow (Turbo boost off)

- ⊃peraung temperature: 14°F ~ 131°F (-10°C ~ 55°C), I
   Storage temperature: -40°F ~ 176°F (-40°C ~ 80°C)
   Storage humidity: 5 ~ 95% @ 40°C, non-condensing
   Anti-vibration: SSD: Random, 3.5 Grms, 5 ~ 500 Hz
   Anti-shock: SSD: 50 G @ wall mount, half-sine, 11 ms
   Certification: CE/FCC class A

Scan this QR code to view the product All details, up-to-date prices and availability

