

Item no.: MS88SF2-3_1

MS88SF2-3Y40AIR_CONFIG1 - Bluetooth Low Energy Module, U.FL Connector, Config 1

from **9,90 EUR**

shipping weight: 0.10 kg
Manufacturer: MINEW Technologies



Product Description

MS88SF2-3 - Bluetooth Low Energy Module, U.FL Connector, Config 1

The MS88SF21 module is an advanced, compact size, highly flexible, ultra-low power wireless BLE 5.0 module based on Nordic nRF52840 SoC with an optimized and complete radio design of 2 types of antennas available: PCB antenna or u.FL (IPEX) connector for an external antenna. MS88SF2 series brings out all nRF52840 hardware features and capabilities including USB access, up to +8 dBm transmit power, up to 5.5 V supply considerations, and 802.15.4 (Thread/Zigbee) implementation, Bluetooth 5 long range feature and advanced security capabilities.

- Product variant: MS88SF23-3Y40AIR

- IPEX connector: Yes
 Chip inside: nRF52840
 Bluetooth qualification: v5.0 (Bluetooth Low Energy)
- Bluetooth Low Energy output power EIRP: 8 dBm
 Maximum range: 800 m
- Maximum number Of connections: 8
 Standalone module open CPU: Yes
- Standalone module ope
 UART: 2
 SPI: 7
 Twl (2C compatible): 2
 GPIO: 20
 ADC: 4

- Minimum supply: 1.7 M
 Maximum supply: 5.5 M
 Maximum temperature: 85°C

- Minimum temperature: -40°C
 Size: 23.2 x 17.4 x 2 mm
 Config 1: 2.5-5V to VDDH, USB available



