

Item no.: TSW210 **TSW210 - Unmanaged Industrial Switch (no PSU)**





Product Description

Teltonika TSW210 - Unmanaged Industrial Switch

The TSW210 is an industrial unmanaged switch for centralizing your resources. It is equipped with 2x SFP ports for long-range fiberoptic communication and 8x Gigabit Ethernet ports with of up to 1000 Mbps download/upload speed. The durable, rugged aluminum housing with DIN rail and surface mounting options makes the TSW210 perfect for industrial settings. It has a 2-pin industrial DC power socket with an input voltage range of 7-57 V DC. Hardware

- Power connector: 2-pin industrial DC power socket
 Input voltage range: 7-57 V DC
 Power consumption: Idle: 1,03 W; Max.: 3,71 W
 Ethernet: 8x 10/100/1000 Mbps Ethernet ports
 SFP: 2x SFP ports for optical interfaces
 Status LEDs: 16x Ethernet, 1x power, 2 x SFP activity
 Ingress protection rating: IP30
 Operating temperature: -40°C to 75°C
 Housing: Aluminum housing with wall or DIN rail mounting options and grounding capability
 Dimensions: 132 x 44.2 x 95.1 mm
 Weight: 500 g

Weight: 500 g
Installation: Desktop, wall or DIN rail mountable (additional kit needed)

Performance Specifications

- Bandwidth: 20 Gbps
- Packet buffer: 128 KB
 Jumbo frame support: 9216 bytes
 MAC address table size: 2K entries
- Auto MDI/MDI-X cable detection: Yes

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

