

Item no.: 351649

TSW304 - DIN Rail Switch (no PSU)

90,88 EUR

Item no.: 351649
shipping weight: 0.30 kg
Manufacturer: Teltonika



Product Description

TSW304 - DIN Rail Switch (no PSU)

TSW304 is Teltonika Networks' first unmanaged switch with an integrated, built-in DIN rail mount. It is equipped with four Gigabit Ethernet ports supporting the IEEE 802.3, IEEE 802.3u, and 802.3az Ethernet standards.

Designed with easy installation in mind, the TSW304 features a compact size with a shock-resistant casing to go along with its integrated DIN mount. It has 10/100/1000 Mbps Ethernet ports for economical, high-bandwidth solutions to provide reliable data throughput. It features a 2-pin industrial power socket and a wide range of supported power supply voltages (7-57 V DC and 9-40 V AC).

Hardware

- Powering option: 2-pin power socket, 7 - 57 V DC/9 - 40 V AC
- Power consumption: Idle: < 0.26 W, max.: < 1.44 W
- Ethernet: 4x 10/100/1000 Ethernet ports
- Status LEDs: 8x Ethernet, 1x power
- Ingress protection rating: IP30
- Operating temperature: -40°C to 75°C
- Housing: Aluminium housing with wall or DIN rail mounting option and grounding capability
- Installation: DIN rail mountable (no additional kit needed)

Performance Specifications

- Dimensions: 102 x 25 x 81.5 mm
- Weight: 210 g
- Bandwidth: 8 Gbps
- Jumbo frame support: 9216 bytes
- Packet buffer: 128 KB
- MAC address table size: 2K entries
- Auto MDI/MDI-X cable detection: Yes

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

