

Item no.: 354772

8070VR-030W - Patchcable Cat.7, S/FTP, 3m, white

from **9,00 EUR**

Item no.: 354772
shipping weight: 0.10 kg
Manufacturer: VARIA Group

Product Description

The last metre: You have already laid a patch cable in your rooms, for example behind shelves, under laminate or behind skirting boards. Until now, the length was sufficient to reach your device, but after rearranging the furniture, the existing cable is no longer sufficient. You are missing the "last metre". Instead of replacing the entire patch cable, simply connect a patch cable extension in the length that suits you to your end device.

Protect your device: For example, protect the socket of your notebook by using this patch cable extension. If the patch cable is plugged in and unplugged frequently, it is not the socket of your notebook that is stressed, but the socket of the extension. This eliminates a possible costly repair of your notebook.

This RJ45 patch cable extension can be used with all conventional devices with RJ45 interface, such as computers, notebooks, DSL modems, routers, switches, game consoles, televisions and many more. The patch cable is double shielded with additional shielding of the wire pairs. This makes it 10 Gigabit-capable, suitable for your fast DSL connection. The patch cable is of course downward compatible with old devices and installations of the categories Cat. 5, Cat. 5e and Cat. 6.

RJ45 plug with RNS®: The RJ45 plug has a latching nose protection (RNS®). This prevents the locking lug on the top of the plug from bending away. The wire pairs consist of 99.99% oxygen-free copper (OFC). This enables an increased signal transmission of the cable.

- RJ45 socket to RJ45 plug with latching nose protection (RNS®)
- Molded socket housing
- Suitable for 10/100/1000/10000 Base-T Ethernet networks (10 Gigabit capable)
- 500 MHz
- Raw cable manufactured according to Cat. 7 specifications
- Shielded RJ45 Cat. 6A connector
- S/FTP cable (shielding foil + braiding)
- PiMF (cores in pairs in metal foil)
- Inner conductor: AWG 26
- Conductor material and contacts made of 99.9% oxygen-free copper (OFC)
- Outer sheath diameter: 6.2 mm
- Flame retardant according to IEC 60332-1
- Assignment 1:1 according to EIA/TIA-568B
- Halogen-free according to IEC 60754-2
- Low smoke according to IEC 61034
- Gold-plated contact surfaces
- Suitable for various devices such as patch panels, switches, routers, modems with RJ45 connection
- Colour: white
- Length: 3 m

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

