

Item no.: 357746

## USB Type-C™ DP 1.4 Docking Station 4K - HDMI / DP 1.4 / USB 3.2 / LAN / PD 3.0

from **221,03 EUR**

Item no.: 357746  
shipping weight: 1.40 kg  
Manufacturer: Delock

### Product Description

This docking station from Delock can be connected to a computer with USB-C™ DP Alt Mode or Thunderbolt™ 3 port and provides a variety of interfaces. Up to three monitors can be operated simultaneously at the DisplayPort outputs and the HDMI output. Four integrated USB ports allow the use of peripherals, and connections for a headset and Gigabit network complete the features.

The product is an MST hub and supports the extended desktop configuration of DisplayPort. This allows multiple monitors to be combined into one large display. The maximum resolution, for simultaneous playback on two or three monitors, depends on the system and the connected hardware.

The docking station has a USB Type-C™ Power Delivery port. If this port is connected to the host device, such as the MacBook, it is charged during operation with up to 85 watts.

The Delock docking station can be operated either horizontally or vertically. A stand is included in the scope of delivery for vertical operation. In addition, the docking station can be attached to a 50 mm VESA mount. The corresponding screw threads are provided on the underside. A security cable can be attached to the Kensington socket to protect the docking station from theft.

- Connectors: 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ jack > 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ jack 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-A jack - BatteryCharging Specification BC1.2 2 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A socket 1 x HDMI-A socket 2 x DisplayPort socket 1 x Gigabit LAN 10/100/1000 Mbps RJ45 socket 1 x Headset 3.5 mm 4 pin jack socket 1 x DC power socket
- Maximum resolution (depending on system and connected hardware): DisplayPort 1.4 Multi-Stream Transport (MST): 1 display: up to 3840 x 2160 @ 60 Hz 2 or 3 displays: up to 1920 x 1080 @ 60 Hz
- Transmission of audio and video signals
- Functions: Mirror or expand, with Mac OS and Chrome only one monitor can be expanded, all others are mirrored
- Supports HDCP 1.4
- Supports HDR
- Output power for host: max. 85 W
- 1 x on/off switch
- 1 x LED indicator
- Security socket (Kensington Lock) for security cable
- Screw thread for 50 mm VESA mount
- Colour: black
- Dimensions (LxWxH): approx. 190 x 85 x 27 mm

#### Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2.37 A
- Output: 20 V / 6.75 A
- Ground outside, plus inside
- Dimensions: inside: ø approx. 5.0 mm outside: ø approx. 7.5 mm length: approx. 12 mm

#### System requirements

- Chrome OS
- Mac OS 10.14.5 or higher
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- Device with a free USB Type-C™ port and DisplayPort
- Alternate Mode or with
- a free Thunderbolt™ 3 port

#### Package contents

- USB-C™ docking station
- Cable USB-C™ plug to USB-C™ plug, length approx. 1 m
- Power supply unit
- Instruction manual

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

