

Item no.: 357825

## GSM/UMTS antenna SMA St. 0.7 - 1.6 dBi 1 m ULA100 omni rigid outdoor white

42,<sup>27</sup> EUR

shipping weight: 0.50 kg Manufacturer: Delock

## Product Description

This GSM/UMTS/LTE antenna can be connected to a GSM/UMTS/LTE device with SMA connector to receive and transmit signals.

- Connectors: SMA connector
- Frequency range: 824 960 MHz, 1710 MHz 2170 MHz
   Antenna gain: 0.7 dBi @ 824 960 MHz, 1.6 dBi @ 1710 MHz 2170 MHz
   Impedance: 50 Ohm
- Polarisation: Linear, vertical
- rouarisation: Linear, vertical
   Horizontal coverage angle: 360
   VSWR: 4.0 @ 824 960 MHz, 2.5 @ 1710 MHz 2170 MHz
   Operating temperature: -10°C ~ 50°C
   Housing material: Polycarbonate

- IP67 protection class
- Screw mounting with 13 mm hole
- Colour: White
  Dimensions (LxD): approx. 77 x 45 mm
  Cable type: Coaxial

- Cable type: ULA 100
  Cable colour: Black
- Cable attenuation: 1.4 dB @ 2500 MHz per metre
  Cable diameter: approx. 2.79 mm
  Cable length: approx. 1 m

## **Specifications**

Scan this QR code to view the product

All details, up-to-date prices and availability

