

Item no.: 362781 ALFA AWUS036AXM WiFi 6/6E, 2x2 Tri-band, Bluetooth v5.2 USB adapter



Item no.: 362781 shipping weight: 0.20 kg Manufacturer: ALFA Network

Product Description

AWUS036AXM is the WiFi 6/6E (802.11ax) 2x2 Tri-band 2.4 GHz / 5 GHz / 6 GHz and Bluetooth v5.2 high-performance USB adapter. AWUS036AXM supports super speeds up to 3000 Mbps (2.4 GHz 600 Mbps, 5 GHz 1200 Mbps, and 6 GHz 1200 Mbps) when used with a compatible WiFi 6E router (there are various stream models of WiFi 6E routers, 800-1200 Mbps will be a more common speed with most routers) and 6 GHz 1200 Mbps. A antenna connector allows changing the higher gain antenna to increase the connection with 2x RP-SMA antenna connector allows changing the higher gain antenna to increase the connection with 2x RP-SMA antenna connector allows changing the higher gain antenna to increase the connection distance. AWUS036AXM also supports the latest Bluetooth v5.2, which provides higher-quality audio over Bluetooth for headphones or speakers. Key features

- 1. MT7921AUN WiFi 6/6E + BT 5.2 combo chip
- USB-A connector support USB 3.2 GEN 1
 2x RP-SMA external antenna connector
- 4. 2x High-gain detachable dipole antenna
- Integrated BT antenna
 LED indicator

Specifications

- Chipset: MediaTek MT7921AUN
- IEEE 802.11 standards: a/b/g/n/ac/ax
- Bluetooth: 5.2

- Bibletouri: 5.2
 Frequency: 2.4 GHz; 5 GHz; 6 GHz;
 Data rate: 2.4 GHz up to 600 Mbps; 5 GHz up to 1200 Mbps; 6 GHz up to 1200 Mbps
 USB connector: USB 3.2 Gen 1 Type-A
 WiFi Antenna: 2x RP-SMA antenna connector with; 2x dual-band high-gain dipole antenna
- BT Antenna: Integrated antenna
 Power consumption: 2.7 Watts (max.)
- Dimensions: 87.4 x 28.5 x 12 mm (34.4 x 11.3 x 4.7 inches)
 Operating temperature: -20° C 70° C (-4° F 158° F)
 Operation voltage: 5 V
- OS support: Windows 10/11 & Linux

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

