

Item no.: 362029

## External USB Type-C™ Combo Enclosure for M.2 NVMe PCIe or SSD - tool-free

from **35,35 EUR**

Item no.: 362029  
shipping weight: 0.10 kg  
Manufacturer: Delock

### Product Description

This enclosure from Delock allows the installation of an M.2 PCIe NVMe SSD or an M.2 SATA SSD in 2280, 2260, 2242 and 2230 format. It can be connected directly to a PC or notebook using the USB-C™ connector.

**Combo enclosure** The great advantage of this Delock M.2 enclosure is that both SATA and PCIe (NVMe) M.2 SSDs can be inserted into the enclosure. The memory is automatically recognised by the chipset and can then be used.

**SSD installation without tools** The special feature of this enclosure is that no tools are needed to install the M.2 SSD. The cover is pushed back and the SSD is inserted into the slot, the SSD is fixed to the board with a rubber nipple and then the cover is put back on until it clicks into place.

**Specification**

- Connectors external: 1x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ connector, internal: 1 x 67 Pin M.2 Key M Slot
- Chipset: Realtek RTL9210B
- Supports M.2 modules in 2280, 2260, 2242 and 2230 format with Key M or Key
- B+M on SATA basis or PCIe (NVMe) basis
- Maximum height of components on the module: 1.5 mm, use of double-sided modules possible
- modules possible
- Supports NVMe Express (NVMe)
- Bootable
- Supports UASP
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Fastening strap for cap
- Dimensions (LxWxH): approx. 115 x 30 x 11 mm
- Hot plug, plug & play

**System requirements**

- Chrome OS 83.0 or higher
- Linux Kernel 3.18 or higher
- Mac OS 10.15.5 or higher
- Windows 8.1/8.1-64/10/10-64
- Device with an available USB Type-C™ port or with an available Thunderbolt™ 3 port

**Package contents**

- M.2 external enclosure
- Instruction manual

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

