

Item no.: APOE-2405

APOE-2405 - 24 V Passive PoE Adapter

11,03 EUR

Item no.: APOE-2405 shipping weight: 0.20 kg Manufacturer: ALFA Network



Product Description

ALFA Network APoE-2405 - 24 V Passive PoE Adapter

The PoE adapter is compatible with the following UBIQUITI products:

- UniFi APUniFi AP-LR
- AirCam
 AirCam Dome
- AirCam MiniAirGrid M2HP
- AirGrid M5HPBullet M2
- Bullet M5
 Bullet Titanium M2HP
 Bullet Titanium M5HP
- Nanostation LOCO M9
 Nanostation LOCO M2
- Nanostation M2
- Nanostation M5
 Nanostation M3
 Nanostation M365
- Output voltage: 24 V
- Output voltage: 24 V
 Output current: 500 mA
 Input voltage: 90 ~ 264 V ac maximum
 Input frequency: 7 ~ 63 Hz
 Input current: 0.3 A maximum
 Inrush current: 30 A maximum
 Ripple: 240 mV maximum
 Hold-up time: 10 ms
 Output current voltaging: Auto recovery.

- Hold-up time: 10 ms
 Over-current protection: Auto recovery
 MTB: 50,000H (at 25°C)
 Short-circuit protection: Auto recovery
 Operating temperature: 0°C ~ 40°C
 Storage temperature: -20°C ~ 485°C
 Relative humidity: 5% 90%
 Safety: CE / FCC

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

