

## Item no.: PRO\_SEC\_24015V PRO-SEC2415V - 2.4 GHz, 15 dBi Sector Antenna Box



## from 58,78 EUR

Item no.: PRO\_SEC\_24015V shipping weight: 1.80 kg Manufacturer: ITELITE

## Product Description

IT ELITE PRO-SEC24015V - 2.4 GHz, 15 dBi Sector Antenna BoxProfessional Sector antenna working in the 2.4 GHz band with 15 dBi gain and vertical polarization. The weatherproof outdoor enclosure with sector antenna has enough space for RouterBOARD or any other electronic equipment. The enclosure is equipped with a special RJ-45 waterproof ethernet connector for an easy connection to network and PoE. Specifically designed for operation under severe weather conditions, since proper materials allow operation without the risk of corrosion even in saltwater environments.

Professional mounting system with 0-15 degrees scale guarantees easy and smooth tilt adjustment, as well as rock-stable operation. This product is ideal for point to multipoint applications for highly professional solutions. Inside the enclosure are suitable posts for models of the MikroTik RouterBOARD 411 and 433 series. Key Features:

- 15 dBi sectorial gain
- Special outdoor weatherproof enclosure
  Highest International Protection Rating IP 66
- High-quality construction
  Minimized sidelobe levels

- Vertical polarization
  Heavy-duty mounting elements
  Easy elevation and tilt adjustment
- Designed for all-weather operation

Applications:

- 2.4 GHz Band Wireless LAN
  IEEE 802.11b/g WLAN Systems
- Point to Multipoint applications

**Electrical Properties** 

- Frequency: 2.4 2.5 GHz
  Gain: 15 dBi
- Polarization: vertical
- Beamwidth deg horizontal: 90°(-3 dB), 120°(-6 dB)
  Beamwidth deg vertical: 12°
- VSWR:
- Impedance: 50 Ohm
- Front to back ratio: > 35 dB
- Lightning protection: DC ground

Mechanical Properties

- Compatible with: RB411 and RB433 series
   Input connector: SMA female, U.FL or MMCX pigtail optional
- Enclosure connector: waterproof ethernet connector
  Outside dimensions: 580 x 150 x 60 mm / 22.8 x 5.9 x 2.4"
- Weight: 2.1 kg / 4.7 lbs

**Enclosure Properties** 

- Technology: Microstrip
  Material: UV-resistant
  Color: white
  International Protection Rating (EN 60529): IP 66
  Min. temperature: -40 °C / -40 °F
  Max. temperature: 80 °C / 176 °F

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

