

Item no.: 336573

63309 - External Industry Hub - 4x USB 3.0 Type-A, with 15 kV, ESD protection

72,45 EUR

Item no.: 336573
 shipping weight: 0.60 kg
 Manufacturer: Delock



Product Description

Delock External Industry Hub - 4x USB 3.0 Type-A, with 15 kV, ESD protection

This solid industry capable USB hub by Delock can be connected to a computer via the USB type A interface. It expands the computer by four USB type A connectors, which supports the USB battery charging specification BC1.2. Thus, connected devices such as smartphones can be charged faster. If necessary, an optional power supply or an optional power cable can be connected to the power socket.

- System requirements: Windows 7/7-64/8.1/8.1-64/10/10-64, Linux Kernel 3.16.x and higher, MAC OS 10.9 and higher; PC or laptop with a free USB type-A port
- Package content: Hub USB, 1x cable USB A male to USB B male, length ca. 1 m, 2x wall mounting brackets, 1x DIN rail mounting (35 mm), 1x 3 pin terminal block, user manual
- Package: Retail box
- Connectors: 1x USB 3.0 type B female > 4x USB 3.0 type A female - battery charging specification BC1.2; 1x 9 - 40 V DC jack; 1x 3 pin terminal power connector
- Chipset: VIA VL811+
- Data transfer rate (up to): SuperSpeed USB 5 Gbps, Hi-Speed 480 Mbps, Full-Speed 12 Mbps, Low-Speed 1.5 Mbps
- LED indicator: 5x
- Ports: USB ports with screw holes
- Housing: Robust metal housing
- Assembly: Removable wallmount brackets
- Power supply: Bus-powered or self-powered
- Flexible power supply: With 9 V to 40 V
- Features: Automatic detection of the input polarity of the power connectors; plug & play
- ESD protection: Up to 15 kV for all ports
- Dimensions (L x W x H): ca. 158 x 80 x 32 mm
- Color: Black
- Power connector: 9 - 40 V; dimensions inside \varnothing ca. 2.1 mm and outside \varnothing ca. 5.5 mm, length is ca. 9 mm

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

