

Item no.: 339048

42609 - External 2.5 Enclosure for M.2 NVMe PCIe SSD with USB 3.1 Gen 2 USB Type-C(TM)

from **59,54 EUR**

Item no.: 339048
shipping weight: 0.60 kg
Manufacturer: Delock



Product Description

Delock External 2.5 Enclosure for M.2 NVMe PCIe SSD with USB 3.1 Gen 2 USB Type-C(TM)

This enclosure by Delock enables the installation of an M.2 PCIe NVMe SSD in 2280, 2260, 2242 and 2230 format, it can be connected via USB to the PC or laptop.

- Enclosure in 2.5 format: The robust metal housing ensures an optimum temperature of the memory. It can also be installed in a standard 2.5 bay.
- Additional protection for SSDs: The enclosure provides various electrical protection mechanisms for the built-in SSD, including short-circuit protection, over heating protection and ESD protection.
- Connectors external: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C(TM) female
- Connectors internal: 1 x 67 pin M.2 key M slot
- Chipset: Asmedia ASM2362
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Bootable
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Metal housing
- Maximum power for modules: 3 A
- Short circuit protection
- Overheating protection
- In-rush current suppression
- ESD protection up to 2 kV
- Dimensions (LxWxH): ca. 100 x 70 x 9.5 mm
- Hot Plug, Plug & Play
- System requirements: Chrome OS, Linux Kernel 3.17 or above, Mac OS 10.14.1 or above, Windows 7/7-64/8.1/8.1-64/10/10-64, Device with a free USB Type-C(TM) port or with a free Thunderbolt(TM) 3 port
- Package content: External enclosure M.2, mounting material, cable USB-C(TM) male to USB-C(TM) male, length ca. 30 cm, 1 x thermal pad, user manual

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

