


Item no.: 343730

SK-GEN4-24PT-PI - 2.4 inch resistive touchscreen Gen4 Picaso

from **82,02 EUR**

Item no.: 343730
 shipping weight: 0.10 kg
 Manufacturer: 4D Systems



Product Description

2.4 inch resistive touchscreen Gen4 Picaso

The 4D Systems SK-gen4-24PT-PI is a starter kit for use with the Raspberry Pi. The kit includes a 2.4-inch display module with integrated Picaso and accessories. The Gen4 module has a resistive touchscreen display and helps to explore the 4D Workshop4 environments and to use all functions to support the user application.

All functions of the display can be used with the designer environment. The microSD card is used to play back images, video and audio. Data logging is done via a programming cable, or the compiled code and PmmC / firmware updates can be downloaded via the adapter. The ViSi and ViSi-Genie environments are similar and have an image-based structure. You need a microSD card and a programming cable. No microSD card or programming cable is required for the serial environment once it has been configured as a serial device. The microSD card can be used for storage or even to switch from one to the other program environment.

The 2.4-inch display module with integrated Picaso, which is compatible with the Raspberry Pi, works with the 4D programming cable, uUSB-PA5-II and 4D Arduino adapter Shield-II. It also works with gen4-PA, gen4-IB and the 4D Serial Pi adapter, which is included in the kit along with other accessories.

Scope of delivery

- Integrated Gen4 display module: gen4-uLCD-24PT display with resistive touch function
- Serial Pi adapter 4D
- Gen4 interface module: gen4-IB
- Gen4 programming adapter: gen4-PA
- Micro SD card, 4 GB
- 150 mm FFC cable: 5-pole flat ribbon cable, socket to socket, with plug / plug adapter
- Quick start guide
- Display size: 2.4 inches
- Controller: Picaso
- Display resolution: 240 x 320
- Display brightness: ?304 nits
- Backlight LEDs: 1 x 4
- Touch: Resistive
- Connector: 30-pin FPC
- Display area (mm): 36.7 x 49
- Module dimensions (mm): 78.4 x 44.8 x 7.4
- Ambient temperature: -15°C to +65°C
- Storage temperature: -30°C to +70°C

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

