

Item no.: 354385 Patch cable fibre optic simplex OS2 (singlemode, 9/125) SC (APC) / SC (APC), LSZH, 7.5 m





shipping weight: 0.10 kg Manufacturer: VARIA Group

## Product Description

Fibre optic patch cables enable different network components to be connected to each other and ensure loss-free data transmission. Different quality classes (OMx/OSx) facilitate the qualitative and functional differentiation of a fibre optic patch cable.

Whether in private households or in demanding and professional application scenarios - with its small 15mm bending radius and very good attenuation values, this simplex patch cable is ideal for connecting FTTH (Fibre To The Home), FTTB (Fibre To The Building), FTTO (Fibre To The Office) and FTTx. For example, it can be used between the house transfer point (HÜP) and the network termination device / optical network termination (ONT) / modem. It can also be used to connect NAS, gaming PC or media centre with router or transfer point (HÜP) and the network termination device / optical network termination (ONT) / modem. It can also be used to connect NAS, gaming PC or media centre with router or transfer point (HÜP) and the network termination device / optical network termination (ONT) / modem. It can also be used to connect NAS, gaming PC or media centre with router or transfer point (HÜP) and the network termination device / optical network termination (ONT) / modem. It can also be used to connect NAS, gaming PC or media centre with router or transfer point (HÜP) and the network termination device / optical network termination (ONT) / modem. It can also be used to connect NAS, gaming PC or media centre with router or transfer point (HÜP) and the network termination (DNT) / modem. It can also be used to connect NAS, gaming PC or media centre with router or transfer point (HÜP) and the network termination (DNT) / modem. It can also be used to connect NAS, gaming PC or media centre with router or transfer point (HÜP) and the network termination (DNT) / modem. It can also be used to connect NAS, gaming PC or media centre with router or transfer point (HÜP) and the network termination (DNT) / modem. modem.

The use of high-quality materials and modern production facilities as well as continuous quality controls during the production process ensure loss-free signal transmission and consistently high quality. Each individual patch cable undergoes testing after assembly. After successful measurement, an individual measurement/test protocol is enclosed with each patch cable.

- Fibre optic simplex patch cable
- Connection 1: SC (APC)
  Connection 2: SC (APC)
- Connection 2: SC (APC)
   Incl. dust protection caps
   Attached bend protection sleeve
   Fibre grade: OS2
   Fibre: G652D
   Eibre thora: Singlement of (425)

- Fibre type: Singlemode 9/125µ
  Cable construction: Simplex
- Cable diameter: 2.0 mm
- Jacket material: Halogen free (LSZH) Min. bending radius: 15 mm •
- •
- wmr. vending radius: 15 mm
  Working temperature: -40 to +85 °C
  Quality: Each cable comes with its own measuring/testing protocol
  Colour: Yellow (OS2)
  Length: 7.5 m

## Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

