


## Item no.: 362028 Delock USB4<sup>™</sup> 40 Gbps Enclosure for 1 x M.2 NVMe SSD - tool-free



Item no.: 362028 shipping weight: 0.20 kg Manufacturer: Delock

## Product Description

This enclosure from Delock enables the installation of an M.2 PCIe NVMe SSD in 2280 format, and can be connected to a PC or notebook with Thunderbolt™ 3, Thunderbolt™ 4 or USB-C™ interface. The robust metal housing with cooling fins ensures optimal temperature of the storage.

USB4™ 40 Gbps

Due to USB4<sup>™</sup> compatibility, the Delock enclosure can be connected to Thunderbolt<sup>™</sup> 3 and 4 ports, as well as to all USB Type-C<sup>™</sup> ports. The maximum data transfer rate depends on the host device.

SSD installation without tools

The special feature of this enclosure is that no tools are required to install the M.2 SSD.

Note

Due to the USB to NVMe controller, the data transfer rate on a USB Gen 2x2 port is only 10 Gbps. Specification

- Connections: external: 1 x USB4<sup>™</sup> 40 Gbps (Gen 3x2) USB Type-C<sup>™</sup> socket internal: 1 x 67 Pin M.2 Key M Slot
   Chipset: Intel JHL7440, Realtek RTL9210B

- Supports M.2 modules in 2280 format with Key M or Key B+M on PCIe (NVMe) basis
   Maximum height of components on the module: 1.5 mm, use of double-sided modules possible
   Supports NVM Express (NVMe)
- Data transfer rate up to 40 Gbps
  LED indicator for power and access

- Metal housing
  Hot plug, plug & play
  Dimensions (LxWxH): approx. 100 x 60 x 14 mm

System requirements

- Android 10.0 or higher
  Chrome OS 90.0 or higher
- iPad Air (4th generation) or higher
  Linux Kernel 5.13 or higher
  Mac OS 12.4 or higher

- Windows 8.1/8.1-64/10/10-64/11

Package contents

- External M.2 enclosure
  Thunderbolt<sup>™</sup> 3 cable, length approx. 50 cm
- 2 x thermal pad
- 2 x rubber nipples Operating instructions

## Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

