

Item no.: 362135

S/PDIF TOSLINK Switch 3 In 1 Out with IR Remote Control and USB Power Supply

from **16,12 EUR**

Item no.: 362135
shipping weight: 0.10 kg
Manufacturer: Delock

Product Description

Brief descriptionWith this TOSLINK switch from Delock, up to three TOSLINK devices can be operated, e.g. on a home cinema system.

Supports HD audio formatsThe switch supports all common 2.0 and 5.1 audio formats such as LPCM, Dolby Digital, DTS Audio and thus offers a sound experience like in the cinema.

High-resolution sampling rateThe switch offers a sampling rate of up to 24 bits and 96 kHz. This means that the sound can be reproduced loss-free in the High-Res Audio range.

High transmission distanceThe switch supports an output transmission distance of up to 40 m via an optical TOSLINK cable with a signal loss of less than 0.2 dB/m.

Manual switching or with IR remote controlThe switch can be switched or switched off by means of buttons on the unit or via the infrared remote control included in the scope of delivery. This allows the inputs to be switched easily and conveniently.

Last Time Working State MemoryThe switch automatically remembers the last working state when switched off and therefore uses the last selected input.

USB power supplyThe switch does not require an additional external power supply unit, power is supplied via the USB cable included in the scope of delivery.

Specification

- Connections - Input, 3x TOSLINK socket S/PDIF, 1x USB type Mini-B socket (5 V power supply), 1x 3.5 mm 3 pin jack socket (infrared input)
- Output - 1x TOSLINK socket S/PDIF
- Supported sampling rates: 32 / 44.1 / 48 / 96 kHz
- Bit rate 16 - 24 bit
- Baud rate: max. 16 Mbps
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supports signal retiming
- On/off switch
- Switch for changing the input source
- 3 x LED display (blue) for selected input
- Plastic housing
- Colour: black
- Dimensions (LxWxH): approx. 61 x 54 x 20 mm
- Voltage: 5 V
- Overvoltage protection
- USB bus power

System requirements

- Digital optical audio signal
- One free USB type-A socket

Package contents

- TOSLINK switch
- USB Type-A to Type Mini-B cable, length approx. 75 cm
- Infrared receiver with 3.5 mm jack plug, cable length approx. 60 cm
- Adhesive pad for infrared receiver
- Remote control
- Operating instructions

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

