

Item no.: A-CAB-109

CAB-109 - Twin-lead Antenna Cable, HDF195, SMA (m)/SMA (f), 10 m

from **59,61 EUR**

Item no.: A-CAB-109
shipping weight: 0.40 kg
Manufacturer: Poynting



Product Description

Poynting A-CAB-109 - Twin-lead Antenna Cable, HDF195, SMA (m)/SMA (f), 10 m

The A-CAB-109 is an HDF 195 twin-lead antenna cable with 10 m length and two SMA (m) to SMA (f) connectors.

Electrical Specifications:

- Capacitance: 24.3 pF/m
- Conductor: Bare copper wire
- Shield coverage: 88 %
- Minimum bend radius: 12.7 mm
- Input impedance: 50 Ohm (nominal)
- Cable loss: 0.25 dB/m at 450 MHz; 0.35 dB/m at 900 MHz; 0.53 dB/m at 2000 MHz; 0.6 dB/m at 2500 MHz

Mechanical Specifications:

- Product dimensions (L x D): 10 m (+/-5%) x 4.95 mm
- Packaged dimensions: 300 mm x 160 mm
- Weight: 0.35 kg
- Packaged weight: 0.37 kg
- Conductor diameter: 0.95 mm
- Dielectric diameter: 2.84 mm
- Inner conductor diameter: 2.96 mm
- Outer conductor diameter: 3.54 mm
- Jacket diameter: 4.95 mm

Environmental Specifications:

- Temperature range (operating): -20° to +70°
- Environmental conditions: Outdoor/indoor
- Operating relative humidity: Up to 98%
- Storage humidity: 5% to 95% non condensing
- Storage temperature: -20° to +70°

Certification Approvals and Standards:

- Cable flammability rating: UL: 1581
- Impact resistance: IK 05
- Product safety: Complies with UL, CE, EN, CSA and IEC standards

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability



