

Item no.: 365029

FT15TMB - 15? Resistive touch monitor, HDMI DP VGA USB

from 438,42 EUR

Item no.: 365029 shipping weight: 5.10 kg Manufacturer: faytech

Product Description

The resistive touch monitors from faytech make your work processes easier and more efficient. These monitors are equipped with numerous features and connections that make them perfect for any industrial or commercial application. Each monitor is manufactured with an industrial LCD panel with backlight (20,000 - 30,000 hours lifetime), 4- or 5-wire resistive touch and anti-glare coating to enhance the user experience. All these devices are wall-mountable or can be placed anywhere with the high-quality stand. The 15-19" monitors feature HDMI, DP and VGA connections. These faytech touch monitors are the perfect choice for a wide range of applications, e.g. for use in POS systems, as control panels in the industrial sector, in kiosk systems, for machine control, in the office and in many other areas.

Product details- HDMI, DP and VGA video ports- USB touch support- 5-wire resistive touch technology- Power supply & plastic desktop mount included- VESA 100 mounting holes on the back- Integrated speakers (2x2w)IP protection class- IP 40LCD panel- Screen diagonal (inch/cm): 15"/38.1 cm- Active display area (cm): 30.56 x 22.95 cm (12.03 in x 9.035 in)- Aspect ratio: 4:3- Physical resolution: 1280x768 px- Maximum displayable external resolution - HDMI, DP: 1920x1080 px- Brightness: 300 (cd/m²)- Contrast: 700:1- Typical response time Tr/Tf: 8/12 (ms)- Viewing angle h/v: 160/160 (°)- Backlight: LED- Backlight lifetime: 30,000 (hours)Touch Panel- Touch technology: 5-wire resistive- Available touch panel drivers: Windows, Linux, Mac, Android- Touch lifetime: 10 million touch in 1 location- Surface hardness level: 3H- Surface treatment: Anti-glareOperating instructions- Operating temperatures: -10°C ~ +60°C (14°F ~ 140°F)- Humidity range (min/max): 10% - 90% RH- Net weight: 3.00 kg / 6.6138 lb- Total weight (incl. packaging): 5.00 kg / 11.023 lb- Housing material: Plastic- Housing size: 370.0 x 287.0 x 55.0 mm (14.56 in x 11.29 in x 2.165 in)Power consumption- Power indicator: Green LED- Power supply: 100-240 V ACDC active switching; 12 V DC-Out- Operating voltage: 12 V- Power consumption: 15 W- Standby power consumption: 1 WExternal connections- Video: 1x HDMI, 1x VGA, 1x DP- Audio chip: 1x PC audio- Touch connections: 1x USB- Other connections: 1x 12 V DC-In (screwable)Included in delivery- Power supply unit (see power consumption)-Quick start guide- Cables (VGA, USB touch, audio)- Standard stand- Stylus input pen

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

