

Item no.: 365031

FT19TMB - 19" RES TM HDMI-DP-VGA USB

from 459,17 EUR

Item no.: 365031 shipping weight: 5.50 kg Manufacturer: faytech

Product Description

The resistive touch monitors from faytech make your work processes easier and more efficient. These monitors are equipped with numerous features and connections that make them perfect for any industrial or commercial application. Each monitor is manufactured with an industrial LCD panel with backlight (20,000 - 30,000 hours lifetime), 4- or 5-wire resistive touch and anti-glare coating to enhance the user experience. All these devices are wall mountable or can be placed anywhere with the high quality stand. The 15-19" monitors have HDMI, DP and VGA connections. These faytech touch monitors are the perfect choice for a wide range of applications, e.g. for use in POS systems, as control panels in the industrial sector, in klosk systems, for machine control, in the office and in many other areas.

In the industrial sector, in klosk systems, for machine control, in the office and in many other areas.

IP protection class- IP 40LCD panel- Screen diagonal (inch/cm): 19"/48.2 cm- Active display area (cm): 41.22 x 25.91 cm (16.22 in x 10.20 in)- Aspect ratio: 16:10- Physical resolution: 1440x900 px- Maximum displayable external resolution - HDMI, DP: 1920x1080 px- Brightness: 250 (cd/m²)- Contrast: 1000:1- Typical response time Tr/Tf: 1.5/3.5 (ms)-Viewing angle h/v: 170/160 (°)- Backlight: LED- Backlight lifetime: 30,000 (hours)Touch Panel- Touch technology: 5-wire resistive- Available touch panel drivers: Windows, Linux, Mac, Android- Touch lifetime: 10 million touches in 1 place- Surface hardness grade: 3H- Surface treatment: Anti-glareOperating instructions- Operating temperatures: -10°C ~ 60°C (48°F ~ 140°F)- Humidity range (min/max): 10% - 90% RH- Net weight: 4.98 kg / 10.979 lb- Total weight (incl. packaging): 6.60 kg / 14.550 lb- Housing material: Plastic-Housing size: 448.0 x 290.0 x 53.0 mm (17.63 in x 11.41 in x 2.086 in)Power consumption- Power indicator: Green LED- Power supply: 100-240 V ACDC active switching; 12 V DC-Out- Operating voltage: 12 V- Power consumption: 20 W- Standby power consumption: 1 WExternal connections- Video: 1x HDMI, 1x VGA, 1x DP- Audio chip: 1x PC audio-Touch connections: 1x USB- Other connections: 1x 12 V DC-In (screwable)Included in delivery- Power adapter (see power consumption)- Quick start guide- Cables (VGA, USB touch, audio)- Standard stand- Stylus input pen

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

