

Item no.: 365061

## FT15N3350W4G128G - 15" Resistive Touch PC (N3350)

from **1.180,56 EUR**

Item no.: 365061  
shipping weight: 5.10 kg  
Manufacturer: faytech

### Product Description

Ideal for use in industrial and commercial applications: faytech's Touch PC series (fanless operation, no-moving-parts designs and aluminium housing)The Touch PC is powered by faytech's Apollo Lake industrial mainboard. It is powered by the Intel® Celeron® N3350 DualCore processor with up to 2.40 GHz clock frequency. This version is equipped with 4GB RAM (max. 8GB), 128G SSD and Intel's HD graphics chipset and supports Full HD, DirectX 11.1 and OpenGL 4.0. These faytech PCs are the perfect choice for a variety of applications, such as POS systems, industrial control panels, kiosk systems, office/residence automation, digital signage and in areas such as shopping centres, classrooms, hotels and many more.

Product details- Intel® Celeron® N3350 DualCore processor- 4 GB RAM memory, 128 GB industrial SSD- Supports Windows 10 & Linux (32 bit, 64 bit)- Anti-glare front with 3H surface hardness- 5-wire resistive touch technology- High-quality black aluminium housing- Standard power connection (screwable)- Integrated WLANIP protection class- IP 40PC System- Processor/CPU: Intel® Pentium® QuadCore N3350- GPU Graphics: Intel® HD Graphics- Audio chip: Realtek ALC3251 Audio CODEC- Memory: 4 GB DDR4 non-ECC (max. 8 GB)- Removable storage: faytech Industrial 128 GB SSD- Network: 2x Realtek PCIe GB LAN 8111G (1x optional with POE); WLAN- Driver support: Windows 10 + Linux Ubuntu- Pre-installed operating system (OS): Linux UbuntuLCD panel- Screen diagonal (inch/cm): 15"/38.1 cm- Active display area (cm): 30.40 x 22.80 cm (11.96 in x 8.976 in)- Aspect ratio: 4:3- Physical resolution: 1024x768 px- Maximum displayable external resolution - HDMI, DP: 1920x1200 px- Brightness: 300 (cd/m²)- Contrast: 700:1- Typical response time Tr/Tf: 8/12 (ms)- Viewing angle h/v: 160/160 (°)- Backlight: LED- Backlight lifetime: 30,000 (hours)Touch Panel- Touch Technology: 5-wire Resistive- Touch Lifetime: 10 million in one location without failure- Surface Hardness Grade: 3H- Surface Treatment: Anti-glareOperating Instructions- Operating Temperatures: -10°C ~ +60°C (14°F ~ 140°F)- Humidity Range (min/max): 10% - 90% RH- Net Weight: 3.40 kg / 7.4957 lb- Total weight (incl. packaging): 5.30 kg / 11.684 lb- Housing material: Aluminium- Housing size: 368.0 x 288.0 x 58.4 mm (14.48 in x 11.33 in x 2.299 in)Power consumption- Power indicator: Green LED- Power supply: 100-240 V ACDC active switching; 12 V DC-Out- Operating voltage: 12 V- Power consumption: 17 W- Standby power consumption: 1 WInternal connections- 1x SO-DIMM, max. 8 GB, DDR3L 1333/1600/1867 non-ECC, single-channel memory- 3x RS232/RS485 COM ports switchable in BIOS- 2x LCD backlight control/LCD panel power box- 1x 5 V/12 V SATA power connector- 1x 12 V DC power connector (2-pin)- 1x 4-pin SATA power connectorpin SATA power connector- 1x S/PDIF output pin header- 1x 8-bit digital I/O interface- 1x Line-Out/Mic-In header- 1x Front Panel Box header- 1x Serial ATA 6Gb/s- 1x MIPI CSI connector- 1x LVDS socket connector- 2x USB 3.0 box headerExternal connections- 1x 12 V DC-In (screwable)- 1x 12 V 3-Pin DC-In (screwable)- 1x WLAN antenna connection (RP-SMA connector)- 2x USB 2.0- 2x USB 3.0- 1x HDMI- 1x DP- 1x MIC-In & EAR-Out- 2x COM-Port Full-PIN - RS232/485; 5 V/12 V- 2x 10/100/1000Mbit RJ45-Ports- 1x 2.5" module slot, removable SSD includedExpansion slots- 1x mSATA full size (occupied by SSD)- 1x M.2 E-Key slot (occupied by WiFi card)- 1x SATA port- 1x external PCIe x1 straddle portIncluded in delivery- Power supply unit (see power consumption)- Quick start guide- W-LAN antenna (RP-SMA female)

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

