

Item no.: 365019

"15"" PCAP TPC i5-7300 8G 128GB SSD OB 1.1mm CG V4"

from **1.915,82 EUR**

Item no.: 365019
shipping weight: 6.30 kg
Manufacturer: faytech

Product Description

faytech's capacitive PC series stands out from the competition thanks to its fanless operation, IP65 front design, high reliability and elegant finish. The touch PC models have a modern and elegant appearance. Thanks to the edge-to-edge glass surface with faytech's patented silicone frame, the front is protected from water and dirt and therefore fulfils the IP65 standard. In combination with the VESA 100 holes (VESA 400 for 32"+), the aluminium housing back offers the option of attaching the PC securely to various surfaces. The heart of this capacitive touch PC is the extremely powerful Kaby Lake U industrial mainboard. The touch PC is powered by an Intel® Core™ i5-7300U processor with up to 2.60 GHz, 8GB RAM, a 128GB SSD and Intel®'s HD Graphics chipset. faytech PCs are the best choice for a wide range of applications, such as POS or kiosk systems in retail, machine control in the industrial sector or digital signage in shopping centres and hotels.

IP protection class- Front housing IP65 / rear housing IP40 PC System- CPU: Intel® Core™ i5-7300U Processor Kaby Lake- Graphics GPU: Intel® HD Graphics- Audio chip: Realtek ALC3236 Audio CODEC- Memory 8 GB DDR4 non-ECC (max. 16 GB)- Hard disc (replaceable): faytech Industrial 128 GB SSD- Network: 2x Realtek PCIe GB LAN 8111G (1000 Mbps), M.2 E-key Wi-Fi module- Driver support: Win10; Linux; 32bit/64bit- Operating system pre-installed: Linux Ubuntu LCD panel- Screen diagonal (inch/cm): 15/38.10- Active display area (cm): 30.40x22.80- Aspect ratio: 4:3- Physical resolution: 1024x768 px- Maximum displayable external resolution - HDMI, DP: 1920x1080 px- Displayed colours: 16.7M- Brightness: 300 (cd/m²)- Contrast: 700:1- Typical response time Tr/Tf: 8/12 (ms)- Viewing angle h/v: 160/160 (°)- Backlight: LED- Backlight lifetime: 30,000 (hours) Touch Panel- Touch technology: Projected capacitive 10-point multi-touch- Touch port: USB- Touch lifetime: Unlimited- Surface hardness: 7H- Surface treatment: Anti-reflective (chemically etched)- Glass hardening: Chemically hardened Operating instructions- Operating temperatures: -10°C ~ +60°C- Humidity range (min/max): 10% - 90% RH- Net weight: 3.4 kg- Total weight (incl. packaging): 5.30 kg- Housing material: Silicone edge, aluminium IPC rear housing- Housing size: 359.0 x 291.0 x 71.0 mm- Cut-out for mounting brackets (mm) L x H: 335.0 x 274.0- Max. Wall thickness for mounting brackets (mm): 5.0- Number of brackets required: 6- Mounting (rear): VESA 100 Power consumption- Power indicator: Green LED- Power supply: 100-240 V ACDC active switching; 12 V DC-Out- Operating voltage: 12 V- Power consumption: 30 W- Standby power consumption: 1 W External connections- 1x 12V DC-In (screwable)- 1x W-LAN antenna connection (RP-SMA male)- 4x USB 3.0- 1x DP- 1x HDMI- 1x MIC-In & EAR-Out- 1x 10-PIN DIO as RJ45- 2x COM port Full-PIN - RS232/485; 5 V/12 V- 2x COM port 3-Pin - RX, TX, GND; RS232/485; 5 V/12 V- 2x 10/100/1000 Mbit RJ45 connections- 1x 2.5" module slot, replaceable SSD integrated- Internal I/O connections (occupied)- 1x SO-DIMM, max. 16 GB, DDR4 1866/2133 non-ECC, single channel memory- 3x RS232/RS485 COM connections, switchable in the BIOS Expansion slots- 1x mSATA full size (occupied by SSD)- 1x M.2 E-Key slot (occupied by WiFi card)- 1x SATA port- 1x external PCIe x1 straddle port Included in delivery- Power supply unit (see power consumption)- W-LAN antenna (RP-SMA female)- Quick start guide- Standard stand

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

