

Item no.: 365038

FT15TMBCAPOB - 15" Capacitive touch monitor DP-HDMI-VGA USB OB 1.1mm CG

from **498,09 EUR**

Item no.: 365038
shipping weight: 5.40 kg
Manufacturer: faytech

Product Description

The capacitive touch monitors from faytech have a modern, sleek look with their flat, borderless glass fronts, which are water and dust resistant to IP65. These devices have capacitive 10-finger multi-touch, a glass front that reaches up to MoSH 7, the glass surface is anti-reflective (chemical etching) and a variety of connections. All monitors have VESA 75 or VESA 100 screw patterns on the back, while the 12.1" to 21.5" monitors come with their own desk stand. Each unit has an optically bonded touch panel that improves stability, reduces reflection, widens the viewing angle and increases perceived brightness. It also provides resistance to dust particles and generally displays a better image. It is the perfect choice for a variety of applications, including industrial automation, control panels and digital signage. Our touch monitors are the perfect choice for a variety of applications, such as POS systems, control panels in industrial areas, kiosk systems, office/home automation, digital signage and in areas such as shopping centres, classrooms, hotels and many more.

Product details- Anti-glare screen surface (chemically etched)- 10-finger multi-touch capacitive touch panel- 1,1 mm cover glass with 7H surface hardness- Optically connected touch panel with LCD panel- Patented IP65 front with silicone seal- Integrated speakers (2x2W) IP protection class- Front housing IP65/rear housing IP40 LCD panel- Screen diagonal (inch/cm): 15"/38.1 cm- Active display area (cm): 30.40 x 22.80 cm (11.96 in x 8.976 in)- Aspect ratio: 4:3- Physical resolution: 1024x768 px- Maximum displayable external resolution - HDMI, DP: 1920x1080 px- Brightness: 300 (cd/m²)- Contrast: 700:1- Typical response time Tr/Tf: 8/12 (ms)- Viewing angle h/v: 160/160 (°)- Backlight: LED- Backlight lifetime: 30,000 (hours) Touch Panel- Touch technology: Projected Capacitive 10-point Multitouch- Available Touch Panel Drivers: Windows, Linux, Mac, Android- Touch Lifetime: Unlimited- Surface Hardness: 7H- Surface Treatment: Anti-reflective (chemically etched)- Glass Hardness: Chemically Tempered Operating Instructions- Operating Temperatures: -20°C ~ +75°C (-4°F ~ 167°F)- Humidity Range (min./10% - 90% RH)- Net weight: 4.10 kg / 9.0389 lb- Total weight (incl. packaging): 5.50 kg / 12.125 lb- Housing material: Silicone edge front, plastic rear- Housing size: 359.0 x 291.0 x 45.0 mm (14.13 in x 11.45 in x 1.771 in)- Support for mounting brackets: Yes- Cut-out for mounting brackets (L x H): 335.0 x 274.0 mm (13.18 in x 10.78 in)- Number of brackets required: 6- Mounting bracket: VESA 100 Power consumption- Power indicator: Green LED- Power supply: 100-240 V AC DC active switching; 12 V DC-Out- Operating voltage: 12 V- Power consumption: 15 W- Standby power consumption: 1 W External connections- Video: 1x HDMI 1.3 (incl. HDCP), 1x VGA, 1x DP- Audio chip: 1x PC audio- Touch connections: 1x USB- Other connections: 1x 12 V DC-In (screwable) Included in delivery- Power supply unit (see power consumption)- Quick start guide- Cables (VGA, USB touch, audio)- Standard stand

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

