

Item no.: 361266

Delock Thunderbolt™ 3 Docking Station 8K - Dual DisplayPort / USB / LAN / SD / Audio / PD 3.0

from **238,54 EUR**

Item no.: 361266
shipping weight: 1.10 kg
Manufacturer: Delock

Product Description

This Thunderbolt™ 3 docking station from Delock can be connected to a computer with a Thunderbolt™ 3 port and provides a variety of interfaces. Up to two monitors can be operated simultaneously at the DisplayPort outputs. Four integrated USB ports enable the use of peripheral devices, connections for a headset and Gigabit network, as well as SD and Micro SD slots complete the equipment.

Thunderbolt™ Certified

Multi-Stream Transport (MST) The product is an MST hub and supports the extended desktop configuration of DisplayPort. This allows multiple monitors to be combined into one large display. The maximum resolution, for simultaneous playback on two or three monitors, depends on the system and the connected hardware.

USB Power Delivery (USB PD 3.0) support up to 60 watts The docking station has a USB Type-C™ Power Delivery port, to which the power supply of the notebook or tablet can be connected to charge it.

Note Only one additional external monitor can be connected to MacBook devices with the M1 chipset.

Connectors:

- 1 x Thunderbolt™ 3 female >
- 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ jack
- 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A socket - Battery Charging

Specification BC1.2

- 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A jack
- 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A jack
- 2 x DisplayPort socket
- 1 x Gigabit LAN 10/100/1000 Mbps RJ45 jack
- 1 x Headset 3.5 mm 4 pin jack socket
- 1 x SD slot
- 1 x Micro SD slot
- 1 x DC power socket
- Chipset: Intel Titan Ridge
- Maximum resolution (depending on system and connected hardware)

with DSC:

- Single Display 7680 x 4320 @ 30 Hz
- Dual Display SST 3840 x 2160 @ 60 Hz + 3840 x 2160 @ 60 Hz
- Dual Display MST 7680 x 4320 @ 30 Hz + 3840 x 2160 @ 60 Hz

without DSC:

- Single Display 3840 x 2160 @ 60 Hz
- Dual Display SST 3840 x 2160 @ 60 Hz + 3840 x 2160 @ 60 Hz
- Dual Display MST 3840 x 2160 @ 60 Hz + 3840 x 2160 @ 60 Hz
- Transmission of audio and video signals
- Functions: Mirror or expand
- Supports HDCP 2.2
- Supports HDR
- Jack socket: automatic recognition OMTP or CTIA standard
- SD / Micro SD Slot: Supports SD 3.0 (UHS-I), SD 4.0 (UHS-II)
- Plug & Play
- Output power for host: max. 60 W
- Colour: grey
- Dimensions (LxWxH): approx. 147 x 80 x 17 mm

Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 3.0 A
- Output: 20 V / 6 A
- Ground outside, plus inside
- Dimensions:
- inside: ø approx. 3.0 mm
- outside: ø approx. 4.5 mm
- Length: approx. 10 mm

System requirements

- Mac OS 10.15.3 or higher
- Windows 8.1/8.1-64/10/10-64
- PC or notebook with a free Thunderbolt™ 3 port

Package contents

- Thunderbolt™ 3 docking station
- Thunderbolt™ 3 cable, length approx. 50 cm
- Power supply unit
- Operating instructions

Specifications

**Scan this QR code to
view the product**

All details, up-to-date
prices and availability

