

Item no.: 373647

## 61843 - Navilock NL-622MP serial MD6 GPS receiver outdoor marine

## from **99,94 EUR**

Item no.: 373647 shipping weight: 0.30 kg Manufacturer: Delock

## Product Description

The GPS receiver with the u-blox 6 SuperSence® chipset receives WAAS and EGNOS data in addition to GPS. The MD6 universal connector enables the connection of optional USB or serial connection cables. The NL-622MP GPS receiver was specially developed for mounting on white surfaces (boat, motorhome, bus, etc.). Thanks to its white housing, it blends unobtrusively into the vehicle design.

Specification- u-blox 6 GPS SuperSense® high performance chip- GPS receiver with MD6 Navilock connector(USB or serial connection cable optionally available)- Internal patch antenna- Central mounting thread with centred cable- Frequency: L1, 1575.42 MHz, C/A Code: 1.023 MHz- Processes signals from up to 50 satellites simultaneously- Supports AssistNow Offline (14 days almanac data), AGPS,WAAS, EGNOS, MSAS, NMEA 0183 protocols: GGA, GSV, RMC, VTG- Baud rate: 9600 (configurable up to 115200)- Update rate: up to 5 Hz- Sensitivity: max. -162 dBm- Waterproof housing (IPXT)- Operating temperature range: -20°C ~ 60°C- Cold start in approx. 25 seconds- Hot start in approx. 1 second- Cable length: 5 m- Position accuracy: 2.5 m CEP (Circular Error Probable) and- 2 m CEP with SBAS- Dimensions: 62 mm x 21 mmSystem requirementsLinux from kernel 2.6, Mac OSX, Windows 98SE/ME/2000/XP/Vista/7/8/10Windows Mobile 2003/5/6For mobile devices with micro USB OTG with optional OTG adapters: Windows 10MD6 connection cable USBWindowsMAC OSXLinuxMD6 connection cable D-Sub9Package contentsNL-622MP receiverMounting materialCD ROMPackagingRetail Box

## Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

