

Item no.: 353736 90059 - PCI Express x4 card to 4 x USB Type-C + 1 x USB Type-A - Low Profile form factor port





## Product Description

PCI Express x4 card to 4 x USB Type-C + 1 x USB Type-A - Low Profile Form Factor

The PCI Express card from Delock expands the PC by five USB 3.2 ports. Various USB devices, such as docking stations, card readers, external enclosures, etc., can be connected to the card.

Sufficient connections - 4 x USB Type-C<sup>™</sup> and 1 x USB Type-A

The PCIe card offers four external USB-C™ ports and one internal USB Type-A port. This allows devices to be connected to each port at 10 Gbps.

- Package contents
  - PCI Express card SuperSpeed USB 10 Gbps
    Low Profile bezel

  - Instruction manual
  - Connections: external: 4 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C<sup>™</sup> socket; internal: 1 x PCI Express x4 (2-lane), V3.0, 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A socket,1 x SATA 15 pin power connector Chipset: Asmedia ASM3142, VIA VL822
  - Data transfer rates up to: SuperSpeed USB 10 Gbps, SuperSpeed USB 5 Gbps, Hi-Speed 480 Mbps, Full-Speed 12 Mbps, Low Speed 1.5 Mbps Backwards compatible with USB 3.0, USB 2.0, USB 1.1 •
  - ٠

  - Powered via SATA power connector
     Electrical power: USB Type-C<sup>™</sup>: max. 15 watts (5 V / 3 A), USB Type-A: max. 4.5 watts (5 V / 0.9 A)
  - Bootable
  - Supports UASP
  - Supports eXtensible Host Controller Interface (xHCI) specification 1.1

  - Supports multiple INs
     Operating temperature: 5 °C ~ 50 °C
     Storage temperature: -20 °C ~ 60 °C
  - Humidity: 20 ~ 80

System requirements

- Linux Kernel 5.4 or higher
  Windows 8.1/8.1-64/10/10-64
  Windows Server 2016
  PC with a free PCI Express x4 / x8 / x16 / x32 slot

Specifications



Scan this QR code to view the product All details, up-to-date prices and availability