

Item no.: 326114

TL-R480T+ - SMB Router, 1x LAN, 1x WAN, 3x LAN/WAN

54,12 EUR

Item no.: 326114
shipping weight: 1.80 kg
Manufacturer: TP-LINK



Product Description

TL-R480T+ - SMB Router, 1x LAN, 1x WAN, 3x LAN/WAN

The TL-R480T+ load balance broadband router is a wise choice for small business. It brings you high return on investment with low overhead. Featured with three changeable WAN/LAN ports, TL-R480T+ supports up to 4 WAN ports, which can satisfy various Internet access requirements through one device. TL-R480T+ integrates multiple load balancing strategies, advanced QoS and strong firewall to provide you with consistent network uptime and reliable Ethernet connectivity. Moreover, it is easy to manage the TL-R480T+ via a web-based utility, which makes building and managing your network more convenient. [Three Changeable WAN/LAN Ports](#)

The TL-R480T+ features three changeable ports that can be set to either LAN or WAN, allowing the router to support up to four WAN ports to satisfy various Internet access requirements through one device. The router also has an integrated smart load balancing function which automatically selects the most efficient line according to load and bandwidth requirements, providing users with consistent network uptime and reliable Ethernet connectivity. [Features](#)

- Up to 4 WAN ports equipped with advanced load balance to guarantee maximum bandwidth and backup capabilities
- Provides extensive client account and network management for administrators with supported PPPoE Server
- Marshals bandwidth resource to specific clients based on their unique application environments

Package contains

- Device
- Power cord
- Rackmount ears
- Patch cable

Connectors and Interfaces

- Serial port: RJ45
- LAN speed: (4) 10/100 Mbps

General

- Concurrent sessions: 30000

Hardware

- RAM [MB]: 64

Physical characteristics

- Design: Rackmount
- Buttons: Reset
- Operating temperature [°C]: 0 up to 40
- Depth [mm]: 180
- Width [mm]: 294
- Height [mm]: 44

Power

- Power type: Mains power (230 V)
- Power via connector/terminal: 230 V AC

Software

- Multiple WAN: Yes
- Default IP address: 192.168.1.1
- Default login and password: admin/admin

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

