

Item no.: 373439

62586 - Navilock NL-8008T Jack TRRS LVTTL Multi GNSS Receiver u-blox 8 1.5 m

from **101,13 EUR**

Item no.: 373439
shipping weight: 0.20 kg
Manufacturer: Delock

Product Description

The jack LVTTL Multi GNSS receiver with the u-blox 8 chipset has a built-in active antenna.

Specification- Connector: 4 pin jack 3.5 mm TRRS LVTTL plug- u-blox 8 UBX-M8030-KT chipset- Frequency GPS: L1, 1575.4200 MHz- Frequency GLONASS: L1, 1602 (k x 0.5625) MHz- Frequency BEIDOU COMPASS: B1, 1561.0980 MHz- Frequency GALILEO E1, 1575.4200 MHz- Frequency QZSS L1, 1575.4200 MHz- Processes signals from up to 72 satellites simultaneously- Supports AssistNow online/offline, SBAS (WAAS, EGNOS, QZSS and MSAS)- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, VTG- Auto Baud Rate bis zu 115200 bps- Update Rate einfach GNSS: 18 Hz (z. e.g. GPS solo)- Update rate multiple GNSS: 10 Hz (e.g. GPS+GLONASS) e.g. GPS+GLONASS)- Sensitivity max. -167 dBm- IPX6 protection class- Magnetic and non-slip housing underside- LED display for GPS status- Operating temperature: -20 °C ~ 60 °C- Power supply: 5 V DC- Current consumption: max. 45 mA- Cold start in approx. 26 seconds- Hot start in approx. 1 second- Position accuracy: 2.5 m CEP (Circular Error Probable) and- 2 m CEP with SBAS- Cable length: approx. 1.5 m- Dimensions (LxWxH): approx. 65 x 45 x 22 mmSystem requirements- One free 3.5 mm jack socketPackage contents- LVTTL receiver- Driver CD- Operating instructions on CD ROM

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

