

Item no.: SC-2402-0214-2152

## US-8-60W - Fully Managed Gigabit Switch

# 103,67 EUR

Item no.: SC-2402-0214-2152

shipping weight: 0.50 kg

Manufacturer: Ubiquiti



### Product Description

#### US-8-60W - Fully Managed Gigabit Switch

- Non-blocking throughput switching performance
- Gigabit Ethernet RJ45 ports
- Robust performance for enterprise networks

**Overview** Build and expand your network with UniFi Switch, part of the UniFi line of products. The new 8-port models feature Gigabit Ethernet ports in a compact form factor. The switches are fully manageable, delivering robust performance and intelligent switching for your networks. **Switching Performance** The UniFi Switch offers the forwarding capacity to simultaneously process traffic on all ports at line rate without any packet loss. For its total, non-blocking throughput, each UniFi Switch supports up to 8 Gbps with a switching capacity of 16 Gbps. **PoE** The US-8 can be powered by 802.3af/at, 48V passive PoE, or the included power adapter. When the US-8 is powered by 802.3at PoE or the included power supply, port 8 supports 48V (2pair) PoE passthrough to deliver up to 12W of power. The US-8-60W is powered by its included power adapter. It has four auto-sensing PoE ports delivering up to 15.4W of power per port.

Model: US-8-60W

- (8) Gigabit RJ45 ports
- (4) auto-sensing IEEE 802.3af PoE ports
- Non-blocking throughput: 8 Gbps
- Switching capacity: 16 Gbps
- Forwarding rate: 11.9 Mpps
- Maximum power consumption: 12 W
- Available in single-pack and 5-pack

#### Specifications

- Dimensions: 148.0 x 99.5 x 30.7 mm (5.83 x 3.92 x 1.21")
- Weight: 432 g (15.24 oz)
- Enclosure Characteristics: SGCC steel
- Total non-blocking throughput: 8 Gbps
- Switching capacity: 16 Gbps
- Forwarding rate: 11.9 Mpps
- Max. power consumption: 12 W (excluding PoE output)
- Max. PoE wattage per port: 15.4 W
- Power method: 48 V DC, max. 2 A
- Supported voltage range: 57 V DC to 44 V DC
- Power supply: External AC/DC adapter, 48 V, 1.25 A
- LEDs: PoE (port 8), speed/link/activity (all ports)
- Networking interfaces: (8) 10/100/1000 Mbps RJ45 ports
- PoE interfaces (4) ports 5, 6, 7, 8; IEEE 802.3af
- ESD/EMP protection:
  - Air: +/- 24 kV
  - Contact: +/- 24 kV
- Operating temperature: -5°C to 45°C (23°F to 113°F)
- Operating humidity: 5 to 95% non-condensing
- Shock and vibration: ETSI 300-019-1.4 Standard
- Certifications: CE, FCC, IC

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

