

Item no.: 373649

## 64138 - Docking station for 1 x M.2 NVMe SSD + 1 x M.2 SATA SSD with SD Express (SD

from **178,87 EUR**

Item no.: 373649  
shipping weight: 0.30 kg  
Manufacturer: Delock

### Product Description

This docking station by Delock enables the operation of an M.2 NVMe and an M.2 SATA SSD, as well as an SD Express memory card and can be connected to a PC, notebook, tablet or smartphone via USB. The included USB cable enables connection to a free USB socket. SD Express Slot The SD Express Slot enables reading and writing of SD Express memory cards. SD, SDHC and SDXC memory cards with UHS-I and UHS-II can also be used. Simultaneous use of all ports All three storage devices can be used simultaneously. Clone function without PC The integrated clone function enables storage devices to be cloned without the use of a PC. It is possible to clone from NVMe to SATA, SD to NVMe, SD to SATA and SATA to NVMe. Ideal test equipment The memory is simply plugged into the robust housing and can be used immediately. No screws, tools or accessories are required, meaning that the SSD can be changed quickly. Power supply unit included The power supply unit, which is included in the scope of delivery, is connected to the USB-C™ power connection and thus supplies the docking station and all connected storage devices with power. Note! If Windows displays an error message after duplicating a bootable operating system M.2 SATA SSD to an M.2 NVMe SSD, missing drivers must still be installed.

Specification- Connectors: 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ socket 2 x 67 Pin M.2 Key M Slot 1 x SD Express Slot 1 x USB Type-C™ socket (power supply)- Chipset: JMicron JMS581- Supports M.2 modules with Key M or Key B+M on PCIe (NVMe) basis- Supports M.2 modules with Key B+M on SATA basis- Supports NVM Express (NVMe)- Supports S.M.A.R.T.- Supports TRIM- Supports DevSleep- Supports Native Command Queuing (NCQ)- Data transfer rate up to 10 Gbps- Supports SD 3.0 (UHS-I), SD 4.0 (UHS-II), SD 5.1 (UHS-II V90), SD 7.1- Supports UASP- LED display for power, access and copy status- Bootable- Function buttons: 1 x clone button 1 x on/off switch 1 x DIP switch for clone mode- Dimensions (LxWxH): approx. 76 x 79 x 18 mm- Hot Plug, Plug & Play Power supply specification- Plug-in power supply- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A- Output: 5.0 V / 3.0 A System requirements- Android 10.0 or higher- Chrome OS 90.0 or higher- iPad Air (4th generation) or higher- Linux Kernel 5.8 or higher- Mac OS 11.2.3 or higher- Surface Pro 7- Windows 8.1/8.1-64/10/10-64- PC or notebook with a free USB Type-A port or- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port Package contents- M.2 Docking station- Cable USB-C™ plug to USB-C™ plug, length approx. 80 cm- Cable USB-C™ plug to USB Type-A plug, length approx. 80 cm- External power supply- Operating instructions

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

