

Item no.: 383089

90103 - LTE GNSS antenna SMA connector 15 - 30 dBi omnidirectional rotatable with tilt joint black

from **20,74 EUR**

Item no.: 383089
shipping weight: 0.10 kg
Manufacturer: Delock

Product Description

This LTE GNSS antenna by Delock enables the use of different LTE bands as well as the worldwide reception of GNSS signals indoors. It is fully compatible with GSM, UMTS, Bluetooth, WLAN 2.4 GHz, ZigBee, DECT, Z-Wave and LoRa. 5G the new mobile communications standard 5G will utilise more and broader frequency spectrums than its predecessors LTE (4G) and UMTS (3G). 5G promises more throughput, capacity and low latency. Specification- Connection: 1 x SMA connector- LTE, GNSS, Bluetooth, GSM, UMTS, WLAN 2.4, ZigBee, Z-Wave, DECT, LoRa- Frequency range: 700 - 960 MHz, 1575.42 MHz, 1710 - 2700 MHz- Antenna gain: 700 - 960 MHz: 1.5 dBi, 1575.42 MHz 1.8 dBi, 2100 - 2700 MHz: 3.0 dBi- Impedance: 50 Ohm- VSWR: 700 - 960 MHz: 3.0, 1575 - 2700 MHz: 2.0- Operating temperature: -40 °C ~ 80 °C- Housing material: ABS- Dimensions (LxWxH): approx. 209 x 42 x 6 mm System requirements- Device with a free SMA connection Package contents- Antenna

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

