

Item no.: 356368

2.4 & 5 GHz AX5400 Wi-Fi 6 Ceiling Access Point

from **181,42 EUR**

Item no.: 356368
shipping weight: 1.40 kg
Manufacturer: TP-LINK

Product Description

- Ultra-fast WLAN with 6 speeds: Simultaneous 574 Mbps on 2.4 GHz and 4804 Mbps on 5 GHz give you 5378 Mbps Wi-Fi speeds
- High-efficiency Wi-Fi 6 : More connected devices can enjoy faster speeds
- Centralised cloud management : Omada SDN integration manages the entire network locally or from the cloud via the web user interface or the Omada app
- 160 MHz channel :Double the data in a single stream with HE160
- Seamless WLAN roaming : Wireless connection between access points for more flexible and easier expansion§
- Omada Mesh : Enables wireless connectivity between access points for extended coverage and flexible deployment§
- PoE+ Powered : Supports both 802.3at PoE+ and DC (adapter included) for flexible installations

HARDWARE FUNCTIONS

- Interface 1x 2.5 Gigabit Ethernet (RJ-45) port (supports IEEE802.3at PoE)
- Reset
- Power supply: 802.3at PoE; 12 V / 1.5 A direct current
- Power consumption: EU: 18.1 W; USA: 19.8 W
- Dimensions (W*D*H) 243 x 243 x 64 mm (9.6 x 9.6 x 2.5 in.)
- Antenna type Internal Omni
- - 2.4 GHz: 2x 4 dBi
- - 5 GHz: 4x 5 dBi
- Mounting Ceiling/wall mounting (kits included)

WIFI FEATURES

- WLAN standards IEEE 802.11ax/ac/n/g/b/a
- Frequency 2.4 GHz and 5 GHz
- Signal rate
- - 5 GHz: Up to 4804 Mbps
- - 2.4 GHz: Up to 574 Mbit/s

OTHER

- Certification CE, FCC, RoHS
- Package contents: EAP670 power supply; ceiling/wall mounting kits; installation guide
- System requirements Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Linux
- Operating temperature: 0-40 ° (32-104 °)
- Storage temperature: -40-70 ° (-40-158 °)
- Operating humidity: 10-90 % relative humidity, non-condensing
- Storage humidity: 5-90 % RH non-condensing

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

