

Item no.: DEC3860 DEC3860 - OPNsense® Rack Security Appliance

from 2.122,30 EUR Item no.: DEC3860

shipping weight: 3.50 kg Manufacturer: Deciso



Product Description

DEC3860 - OPNsense® Rack Security Appliance

This model includes 32 GB DDR4 RAM, 512 GB M.2. Solid State Flash and can handle upto 17.6 Gbps Firewall & 2.5 Gbps IPsec throughput. The ultimate appliance for Intrusion Prevention, Webproxy or Zenarmor (Sensei).

OPNsense is Deciso's fast growing open source firewall and security platform released under an Open Source Initiative approved license. Its rich feature set is combined with the benefits of open and verifiable sources.

All features can be used from within the easy to use graphical interface, equipped with a build-in search feature for quick navigation. Protecting your network has never been this easy with features such as the integrated intrusion prevention system and two-factor authentication for safely connecting mobile users. Software

Preinstalled software: OPNsense®

• License: Open Source + 1 year free Business Edition

Hardware Specifications

- SFP+ ports [10 bps]: 2
 GbE RJ45 ports [10/100/1000 Mbps]: 4
 USB 3.0 ports: 2
- •
- Console port: 1 Internal storage: 512 GB M.2. Solid State Flash
 Memory: 32 GB DDR4

- CPU cores: 8 (max. frequency 3.1 GHz)
 Virtual interfaces (802.1q VLANS): 4093

System Performance

- Firewall throughput: 17.6 Gbps
- Firewall packets per second: 1450 Kpps
 Firewall port to port throughput: 17.6 Gbps
 Firewall port to port packets per second: 1450 Kpps
- Concurrent sessions: 31000000
 New connections per second: 50000

- Firewall latency (average): 100 us
 Firewall policies (recommended maximum): 10000
 IPsec VPN throughput (AES256GCM16): 2.5 Gbps
- IPsec VPN packet per second (AES256GCM16): 220 Kpps
 Threat protection throughput packet per second: ~163 Kpps
- Threat protection throughput: ~2 Gbps
 High availability with state synchronisation: Requires two

Dimensions

- Height x width x length (mm): 44.5 (1U) x 482.6 (19") x 280 (254 excl. panel)
 Height x width x length (inches): 1.75 x 19 x 11 (10 excl. panel)
 Form factor: 19" rackmountable
 Weight (appliance only): 3.43 kg

Environment

- Power requirements: 100-240 V AC, 50-60 Hz
 Maximum current (AC): 2.2 A
 Power consumption (typical): 45 W
 Heat dissipation (typical): 153.6 BTU/hr
 Operating temperature: 0°C to +50°C
 Storage temperature: -20°C to +70°C
 Humidity: 10-90% non-condensing

Regulatory Compliance

• FCC part 15 Class A, CE, RoHS

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

