

Item no.: TRB245 TRB245 000000 - TRB245 - ALL-IN-ONE industrial M2M LTE Cat 4 Gateway

from 189,98 EUR

Item no.: TRB245 shipping weight: 0.20 kg Manufacturer: Teltonika



Product Description

TRB245 - ALL-IN-ONE industrial M2M LTE Cat 4 Gateway

The Industrial LTE Cat 4 Gateway TRB245 is equipped with GNSS receiver, Ethernet port and a durable 16 pin connector block. This Gatewayboard packs all essential features for industry in one package: secure power connector, I/O ports, serial communication, fast and reliable internet connection.

TRB245 can be used to integrate modern and legacy industrial equipment in one solution and with a wide range of software features. Such as SMS control, Firewall, open VPN, IPSec, RMS user can be ensured that data can be reached securely and without compromises. Hardware

- Mobile: 4G/LTE (Cat 4), 3G, 2G
 CPU: Qualcomm, MIPS 24Kc, 650 MHz
 Memory: 16 MBytes Flash, 64 MBytes RAM
 Powering option: 16pin terminal, 9-30 VDC
 SIM: 2x Internal SIM holders (2FF)

- Antenna connectors: 1x SMA for mobile, 1x SMA for GPS
 Ethernet: 1x 10/100 Ethernet port
- GNSS: GPS, GLONASS, BeiDou, Galileo, QZSS
- Gross. Gros, GLOVASS, BEIDOU, Gallieo, QZSS
 Inputs/Outputs: On 16pin socket: 3x Digital input/Digital open collector output (configurable), 1x Analog input
 Serial: 1x RS232, 1x RS485
 Status LEDs: 3 x Connection type, 3x Signal strength, 2x Ethernet, 1x Power
 Operating temperature: -40 °C to 75 °C
 Housing: Aluminium housing with DIN rail mounting option

Software

- Operating system: RutOS (OpenWrt based Linux OS)
 Mobile features: Multiple PDN, Auto APN, Band lock, SIM switch, Operator black/white list, Data/SMS limits
 Network protocols: TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSLv3, TLS 1.3, ARP, PPP, DHCP, Telnet
 Monitoring and Management: WEB UI, CLI, SSH, SMS, TR-069, SNMP, JSON-RPC, MQTT, RMS
 Connection monitoring: Ping Reboot, Wget reboot, Periodic Reboot, LCP and ICMP for link inspection
 Cloud solutions: RMS, FOTA, Telenor, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx
 NTP: NTP Server, NTP Client, Sync with: External NTP server, GNSS, Mobile operator
 GNSS: NMEA forwarding, AVL, Geofencing
 Modbus: TCP slave, TCP master, RTU master, RTU gateway, Modbus over MQTT
 Serial: Console, Over IP, Modem, NTRIP, Modbus
 Administration: Multi user Configuration profiles. Diagnostics. Jons. Configuration backup.

- Administration: Multi user, Configuration profiles, Diagnostics, logs, Configuration backup

Specifications



Scan this QR code to view the product All details, up-to-date prices and availability